
ELECTRICAL BITS - CABLE - CONNECTORS - BULBS ETC








| 0.25W CARBON FILM RESISTORS | | 423 |
|--|----------------|------------|
| ABS BOXES | | 412 |
| ALARM & PANEL INDICATORS | | 425 |
| BOTTLE/CLIP-ON LAMP FITTINGS | | 425 |
| CABLE TIES & CLIPS | | 411 |
| CIGAR LIGHTER ADAPTORS | | 418 |
| CIGAR LIGHTER PLUGS & SOCKE | TS | 418 |
| CLOCK FACES & NUMERALS | | 437 |
| CLOCK MOVEMENTS & HANDS | 436 - | |
| COPPER ELECRIFICATION TAPE | | 410 |
| CROCODILE CLIPS | | 419 |
| DC POWER PLUGS & SOCKETS | | 413 |
| DIN AUDIO CONNECTORS | | 412 |
| DIODES | | 431 |
| D PLUGS & SOCKETS | | 417 |
| EQUIPMENT WIRE | | 410 |
| FUSES & FUSE HOLDERS | | 420 |
| GAUGEMASTER TRACK ACC | _ | 428 |
| GAUGEMASTER TRANSFORMERS | 3 | 428 |
| GRAIN OF RICE BULBS | | 423 |
| GRAIN OF WHEAT BULBS | | 424 |
| HEAT SHRINKABLE SLEEVING | 4.40 | 412 |
| JACK PLUGS & SOCKETS | 412 - | |
| LED PANEL CLIPS & HOLDERS | 404 | 423 |
| LED'S | 421 | |
| LES BULBS & HOLDERS | | 424 |
| MAGNETS | | 435 |
| MAINS POWER CORD SETS | | 417 |
| MES BULBS & HOLDERS | 121 | 425 |
| MICRO SWITCHES MINIATURE PLUGS & SOCKETS | 434 - | |
| MINIATURE PLUGS & SUCKETS MINIATURE PULL SWITCHES | | 419 434 |
| MINIATURE PUSH SWITCHES | 433 - | |
| PECO LECTRICS | 433 - 429 - | |
| PHONO PLUGS & SOCKETS | 429 - | 413 |
| PHOS BRONZE STRIP | | 410 |
| PIN STRIPS & SOCKETS | | 418 |
| POTENTIOMETERS | | 431 |
| POWER SUPPLIES | | 427 |
| PVC INSULATION TAPE | | 412 |
| RC PLUGS & SOCKETS | 414 - | |
| REED SWITCHES | 717 | 435 |
| ROTARY SWITCHES | | 434 |
| SCREENED AUDIO & RIBBON CAL | 3I F | 411 |
| SEEP POINT MOTORS | | 428 |
| SIGNAL/ALARM CABLE | | 411 |
| SLIDE SWITCHES | | 433 |
| SOLAR PANELS | | 425 |
| SOLDERLESS LED CONNECTOR | | 423 |
| SOLDER TAGS | | 419 |
| SPEAKERS & BUZZERS | | 431 |
| STRIP BOARD & MATRIX BOARD | 435 - | 436 |
| SWITCH MODE ADAPTORS | 426 - | |
| TAG STRIPS | 418 - | |
| TERMINAL BLOCKS | | 419 |
| THERMAL CIRCUIT BREAKERS | | 420 |
| TOGGLE SWITCHES | 432 | -433 |
| TRACKSETTA GAUGES | | 430 |
| TUMBLER & ROCKER SWITCHES | | 433 |

COPPER ELECTRIFICATION TAPE

3/16" COPPER ELECTRIFICATION TAPE ideal for connecting low voltage circuits where discreet wiring is desired, such as in dolls houses, under model roads etc. The illustration shows a few applications, but the tape may be equally useful on model boats and planes etc. C.S.A.approx 0.25mm². Max current approx 0.4A.



| CODE | TYPE | PRICE |
|---------|-----------------------------------|--------|
| 522-300 | Copper Tape 3/16" x 25 Foot | £4.99 |
| CET316 | Copper Tape 3/16" x 36yd/108 Foot | £10.99 |
| 522-015 | "Twin" Copper Tape 15 Feet | £9.99 |
| 522-030 | "Twin" Copper Tape 30 Feet | £16.99 |
| | | |

PHOS BRONZE STRIP

PHOS BRONZE STRIP fine phos bronze strip for making pick ups on model railway locomotives etc. 1/16" x .005". Supplied in a pack containing 10×6 " strips.

| CODE | TYPE | PRICE |
|-------|---|-------|
| S1220 | 1/16" x .005 Phos. Bronze Strip 6" 10pk | £3.50 |

EQUIPMENT WIRE

MINIATURE STRANDED EQUIPMENT WIRE 10/0.1mm. A flexible wire, which is ideal for signal interconnection within apparatus where it is necessary to pack a large number of wires into small spaces. 10/0.1mm copper conductor. Overall diameter 0.9mm. Rating 1000V rms, 0.5A. Available in 5 metre lengths and 100metre drums. 11 colours:- Black(BK), Blue(BU), Green(GN), Orange(OR), Red(RD), White(WH) and Yellow(YL), Brown(BR), Grey(GY), Pink(PK) and Violet(VT).

* Order by CODE + COLOUR/COLOURS *

| CODE | TYPE | PRICE |
|---------|---|-------|
| 522-400 | Mini Equip Wire 10/0.1mm 5M (+COLOUR) | £0.75 |
| 522-405 | Mini Equip Wire 10/0.1mm 100M (+COLOUR) | £4.99 |

STRANDED HOOK-UP WIRE 7/0.2mm. A flexible wire for general interconnection within apparatus etc. 7/0.2mm copper conductor. Overall diameter 1.4mm. Rating 1kV rms 1.4A @ 70°C. 11 colours:- Black(BK), Blue(BU), Green(GN), Orange(OR), Red(RD), White(WH) and Yellow(YL), Brown(BR), Grey(GY), Pink(PK) and Violet(VT). Available in 10 metre lengths and 100 metre drums.

*Order by CODE + COLOUR/COLOURS *

| CODE | TYPE PRICE |
|--------|---|
| 10M7/2 | Hook-up Wire 7/0.2mm 10M(+ COLOUR) |
| 100M72 | Hook-up Wire 7/0.2mm 100M (+COLOUR)£6.99 |
| 100MMP | 3 X 100M DRUMS (+ COLOURS)£19.99 |
| 111MMP | 11 X 100M Drums (ANY MIX OF COLOURS) £69.00 |

STRANDED HOOK-UP WIRE 16/0.2mm. A flexible wire for general purpose and heavy duty interconnection within apparatus. 16/0.2mm copper conductor. Overall diameter 1.6mm. Rating 1kV rms 3A. Available in 10 metre lengths and 100 metre drums. 11 colours:- Black(BK), Blue(BU), Green(GN), Orange(OR), Red(RD), White(WH) and Yellow(YL), Brown(BR), Grey(GY), Pink(PK) and Violet(VT).

* Order by CODE + COLOUR/COLOURS*

| CODE | TYPE | PRICE |
|--------|--------------------------------------|--------|
| 10M162 | Hook-up Wire 16/0.2mm 10M (+ COLOUR) | £1.95 |
| 100162 | Hook-up Wire 16/0.2mm 100M (+COLOUR) | £13.99 |

STRANDED HOOK-UP WIRE 32/0.2mm a flexible wire for general purpose heavy duty interconnection within apparatus. 32/0.2mm copper conductor, overall diameter 2.6mm. Rating1500V @ 6A. Available in 10 metre lengths and 100 metre drums.

* Order by CODE + COLOUR/COLOURS*

| TYPE | PRICE |
|----------------------------------|--|
| Hook-up Wire 32/0.2mm Black 10M | £3.85 |
| Hook-up Wire 32/0.2mm Black 100M | £26.99 |
| Hook-up Wire 32/0.2mm Red 10M | £3.85 |
| Hook-up Wire 32/0.2mm Red 100M | . £26.99 |
| | TYPE Hook-up Wire 32/0.2mm Black 10M Hook-up Wire 32/0.2mm Black 100M Hook-up Wire 32/0.2mm Red 10M Hook-up Wire 32/0.2mm Red 100M |

EXTRA FLEXIBLE WIRE a very flexible wire that is ideal for test leads and as interconnection wires which are frequently being moved. 55/0.1mm copper conductor. Overall diameter 2.8mm. Max current rating 6A. Sold per metre (max 25M) or on 25 metre drums. Available in 6 colours:- Red(**RD**), Black(**BK**), Blue(**BU**), Green(**GN**), White(**WH**) and Yellow(**YL**).

* Order by CODE + COLOUR/COLOURS*

| CODE | TYPE | PRICE |
|--------|--------------------------------------|-------|
| 1M551 | Extra Flex Wire per Metre (+ COLOUR) | £0.35 |
| 25M551 | Extra Flex Wire 25M Drum(+ COLOUR) | £5.99 |

BELL WIRE a solid cored low voltage bell wire. Figure "8" 2 cores of 1/0.5mm copper conductor. White sheathed. Overall size 4 x 2mm. Supplied by the metre and 100 metre drums.

| CODE | TYPE | PRICE |
|---------|---------------------|--------|
| 520-703 | Bell Wire/Metre | £0.25 |
| 520-705 | Bell Wire 100M Reel | £17.99 |

LOUDSPEAKER 2 CORE FLEX a flexible figure "8" 2 core cable rated 1 amp at 60v. Two cores of 7/0.14mm copper conductor. Grey sheathed with line for polarity identification. Overall size 4 x 1.6mm. Supplied by the metre and 100 metre drums.

| CODE | TYPE PRIC | Ε |
|---------|---|----|
| 520-700 | 1A 2 Core Loudspeaker Flex /metre£0.2 | 25 |
| 520-701 | 1A 2 Core Loudspeaker Flex 100M Reel£16.9 | 99 |

LOUDSPEAKER 2 CORE FLEX a flexible figure "8" 2 core cable rated 2.5 amp at 60v. Two cores of 13/0.2mm copper conductor. Grey sheathed with line for polarity identification. Overall size 2.0 x 4.0mm. Supplied by the metre and 100 metre drums.


| CODE | TYPE | PRICE |
|---------|--|--------|
| 520-707 | 2.5A 2 Core Loudspeaker Flex /metre | £0.34 |
| 520-709 | 2.5A 2 Core Loudspeaker Flex 100M Reel | £24.99 |


SIGNAL/ALARM CABLE

SIGNAL CABLE a range of flexible multicore cables for a variety of low voltage uses ideal for alarm installations and signalling. Easy to install multi cores neatly and efficiently. Available in three versions 4 core 7/0.2mm tinned copper conductors, 6 core 7/0.2mm tinned copper conductors and 8 core 7/0.12mm all types are overall sheathed in white PVC. Supplied by the metre.

Core Colours

4 Core Red, Black, Blue, Yellow 6 Core Red, Black, Blue, Yellow, Green, White, 8 Core Red, Black, Blue,





RIBBON CABLE

8 Core Signal Cable White 100M Reel.....£54.99

RIBBON CABLE a grey cable with identification strip for use with all styles of IDC connectors. It consists of parallel stranded tinned copper wire conductors laminated between layers of PVC film to form a flat ribbon cable which may be split into any number of ways. Conductor spacing 0.05in. Conductor - 7/0.127mm tin plated copper, rating 1A 300V per conductor. Supplied in multiples of 1 foot. Maximum length 100 feet. Rainbow cable is available in 10 and 20 way cable.

| CODE | TYPE | PRICE |
|---------|----------------------------------|-------|
| 520-602 | Grey Ribbon Cable 9 Way/Foot | £0.20 |
| GRC10W | Grey Ribbon Cable 10 Way/Foot | £0.29 |
| 520-604 | Grey Ribbon Cable 14 Way/Foot | £0.30 |
| GRC16W | Grey Ribbon Cable 16 way/Foot | £0.30 |
| GRC20W | Grey Ribbon Cable 20 Way/Foot | £0.37 |
| GRC26W | Grey Ribbon Cable 26 Way/Foot | £0.59 |
| 520-606 | Grey Ribbon Cable 34 Way/Foot | £0.63 |
| 520-608 | Grey Ribbon Cable 40 Way/Foot | £0.80 |
| 520-610 | Grey Ribbon Cable 50 Way/Foot | £0.99 |
| 520-612 | Grey Ribbon Cable 60 Way/Foot | £1.32 |
| 520-614 | Rainbow Ribbon Cable 10 Way/Foot | £0.50 |
| 520-616 | Rainbow Ribbon Cable 20 Way/Foot | £1.00 |

SCREENED AUDIO CABLE

2 CORE INDIVIDUALLY SCREENED AUDIO CABLE a twin individually screened cable in a figure "8" format. Stranded copper conductors, copper lap screens with an extra flexible black PVC outer sheath. Ideal for phono leads and general purpose audio applications. 2 x 10/0.1mm, O.D. 6.0 x 3.0mm. Supplied by the metre.



CABLE TIES

CABLE TIES white nylon cable ties, non-releasable ratchet lock action.



| CT1401 | 1 140mm | 3.2mm | 35mm | 18Kg | |
|---------|------------|----------|-------------|------|-------|
| CODE | TYPE | | | | PRICE |
| 520-399 | Cable Ties | 80mm 50 | Pack | | £0.50 |
| 520-400 | Cable Ties | 80mm 100 |) Pack | | £0.99 |
| CT0100 | Cable Ties | 100mm 50 |) Pack | | £0.60 |
| CT1001 | Cable Ties | 100mm 10 | 00 Pack | | £1.00 |
| CT0450 | Cable Ties | 100mm BI | ack Pack of | 100 | £1.00 |
| CT0140 | Cable Ties | 140mm 50 |) Pack | | £1.25 |
| CT1401 | Cable Ties | 140mm 10 | 00 Pack | | £1.99 |

CABLE TIE BASES self adhesive bases which accept cable ties, they also has a 5mm fixing hole as an alternative. sizes available:-19 x 19mm - max tie width 3.6mm.

28 x 28mm - max tie width 4.8mm.

| CODE | TYPE | PRICE |
|--------|--------------------------------------|-------|
| CTB559 | Cable Tie Base 19 x 19mm Pack of 25 | £1.99 |
| CTB560 | Cable Tie Base 19 x 19mm Pack of 50 | £3.50 |
| CTB561 | Cable Tie Base 19 x 19mm Pack of 100 | £5.65 |
| CTB562 | Cable Tie Base 25 x 25mm Pack of 25 | £2.75 |
| CTB563 | Cable Tie Base 25 x 25mm Pack of 50 | £3.99 |
| CTB564 | Cable Tie Base 25 x 25mm Pack of 100 | £7.99 |

SPIRAL CABLE WRAPPING a pre-formed plastic spiral cable binding which may be expanded by wrapping round cable forms. Rigidity of the complete bundle can be adjusted by altering closeness of the spiral. Natural colour 6mm dia, maximum bundle diameter 50mm.

HOOK & LOOP CABLE TIES multi-use high quality nylon hook & loop cable ties. Including an eyelet for

feeding onto cable. Available in 150mm, 300mm and 450mm lengths, in packs of 10. Colour black.

| CODE | TYPE | PRICE |
|---------|---|-------|
| 02-8741 | Hook & Loop Cable Ties 150mm Pack of 10 | £2.35 |
| 02-2543 | Hook & Loop Cable Ties 300mm Pack of 10 | £2.85 |
| 02-5071 | Hook & Loop Cable Ties 450mm Pack of 10 | £3.25 |

ALUMINIUM CABLE CLIPS

SELF ADHESIVE ALUMINIUM CABLE CLIPS self adhesive cable clips to enable easy fixing to clean dry surfaces allowing fixing to surfaces where traditional cable clips cannot be used. Available in two sizes. Supplied in packs of 25.

Cable dia.

6.3mm Base 16 x 11mm. 10.0mm Base 19 x 16mm.

| CODE | TYPE | PRICE |
|---------|------------------------------|-------|
| 520-020 | Aluminium Cable Clips 6.3mm | £2.99 |
| 520-025 | Aluminium Cable Clips 10.0mm | £3.99 |

PVC INSULATION TAPE

INSULATION TAPE good quality electrical grade self-adhesive

PVC insulating tape. 19mm x 4.5M and 33M reels. Nominal thickness 0.15mm. Available in a range of colours. Conforms to BS3924



| CODE | TYPE | PRICE |
|--------|----------------------------|-------|
| ITBK10 | Insulation Tape Black 4.5M | £0.45 |
| ITR020 | Insulation Tape Red 4.5M | £0.45 |
| IT6040 | Insulation Tape Black 33M | £1.85 |
| | | |

HEAT SHRINKABLE SLEEVING

HEAT SHRINKABLE SLEEVING a highly flexible polyolefin tubing which will shrink in a ratio of 2:1 by heating above 120°C. Continuous operation from -55°C to +135°C with short duration capability to +300°C. Typical applications include insulation and strain relief on electrical connections. Bore size is quoted before shrinking. Colour Black. Further colours available:- Clear(CL), Red(RD), Yellow(YL) and Blue(BU) at the same prices as below, please order with code and colour. All supplied in lengths of 1.2M.

| CODE | TYPE | PRICE |
|--------|--------------------------------------|-------|
| HSB016 | Heat Shrink Sleeve 1.6mm (+ COLOUR) | £1.50 |
| HSB024 | Heat Shrink Sleeve 2.4mm (+ COLOUR) | £1.65 |
| HSB032 | Heat Shrink Sleeve 3.2mm (+ COLOUR) | £1.75 |
| HSB048 | Heat Shrink Sleeve 4.8mm (+ COLOUR) | £2.15 |
| HSB064 | Heat Shrink Sleeve 6.4mm (+ COLOUR) | £2.50 |
| HSB095 | Heat Shrink Sleeve 9.5mm (+ COLOUR) | £2.99 |
| HSB127 | Heat Shrink Sleeve 12.7mm (+ COLOUR) | £3.45 |

3:1 HEAT SHRINKABLE SLEEVING general purpose black highly flexible polyolefin tubing which will shrink in a ratio of 3:1 by heating above 125°C. Continuous operation from -75°C to +135°C. Typical applications include insulation and strain relief on electrical connections, building of wire bundles and identification and colour coding. Bore size is quoted before shrinking. Black only. Supplied in lengths of 1.2M.

| CODE | TYPE | PRICE |
|---------|----------------------------------|-------|
| 520-220 | 3:1 Heat Shrink Sleeve 1.5mm dia | £1.75 |
| 520-225 | 3:1 Heat Shrink Sleeve 3.2mm dia | £1.99 |
| 520-230 | 3:1 Heat Shrink Sleeve 6.0mm dia | £2.99 |

ADHESIVE LINED HEAT SHRINKABLE SLEEVING a general purpose black highly flexible polyolefin tubing with adhesive lining which will shrink in a ratio of 3:1 by heating above 125°C. As the sleeving is heated the sleeve shrinks and the adhesive melts to form a seal and encapsulates the components contained within. Typical applications include insulation and strain relief on electrical connections, splicing cable forms and terminating other forms of sleeving such as our expandable braided sleeving. Bore size is quoted before shrinking. Colour Black. Supplied in lengths of 1.2M.

| CODE | TYPE | PRICE |
|---------|---------------------------------------|-------|
| 520-260 | 3:1 Adh. Heat Shrink Sleeve 3.2mm dia | £3.99 |
| 520-265 | 3:1 Adh. Heat Shrink Sleeve 4.8mm dia | £4.50 |

FREE PARKING FOR 2 HOURS OUTSIDE OF OUR SHOP

ABS BOXES

BLACK ABS BOXES a range of small boxes moulded in black

ABS which is easily drilled or punched but very strong. The lids are retained by 4 self-tapping screws. The two largest sizes have PCB slots. Dimensions are L x W x H.



| CODE | TYPE | PRICE |
|---------|--------------------------------|-------|
| 600-030 | Black ABS Box 75 x 50 x 25mm | £1.79 |
| 600-035 | Black ABS Box 110 x 56 x 20mm | £2.35 |
| 600-040 | Black ABS Box 100 x 75 x 40mm | £2.75 |
| 600-045 | Black ABS Box 150 x 100 x 55mm | £4.99 |

MINIATURE MULTIPURPOSE ABS BOXES a range of miniature boxes manufactured in matt black ABS with the smallest measur-

ing just 34 x 16 x 24mm. Supplied with 4 black No. 2 self-tapping screws for lid fixing. Can easily be drilled or punched for a variety of miniature applications.



| CODE | TYPE | PRICE |
|---------|--|-------|
| 600-156 | Mini Multipurpose ABS Box 34 x 16 x 24 | £1.45 |
| 600-157 | Mini Multipurpose ABS Box 40 x 18 x 28 | £1.50 |
| 600-158 | Mini Multipurpose ABS Box 46 x 20 x 32 | £1.65 |
| 600-159 | Mini Multipurpose ABS Box 54 x 23 x 38 | £2.25 |
| 600-160 | Mini Multipurpose ABS Box 64 x 25 x 43 | £2.40 |
| 600-161 | Mini Multipurpose ABS Box 74 x 29 x 49 | £2.50 |

DIN AUDIO CONNECTORS

DIN CONNECTORS a range of insulated DIN plugs matching the socket types below. Black PVC body.

| | W | W | ~ | 600 | () | |
|--------|-------|-----------|-----------|---------|-------|-----------|
| | 4 way | 5 way 45" | 5 way 60" | 7 way | 8 way | |
| CODE | TY | PE | | | | PRICE |
| CON220 | 4 P | in DIN | Plug. | | | £0.50 |
| CON230 | 5 P | in DIN | Plug | 45°(180 |)°) | £0.60 |
| CON240 | 5 P | in DIN | Plug | 60° (24 | 0°) | £0.60 |
| CON260 | 6 P | in DIN | Plug. | | | £0.65 |
| CON280 | 8 P | in DIN | Plua. | | | £0.80 |

DIN CHASSIS MOUNTING SOCKETS to suit the above insulated DIN plugs, also suitable for screened DIN connectors. Panel cut out required 16mm.

| TYPE | PRICE |
|-----------------------------|--|
| 5 Pin DIN Socket 45° (180°) | £0.60 |
| 6 Pin DIN Socket | £0.75 |
| 8 Pin DIN Socket | £0.80 |
| | TYPE 5 Pin DIN Socket 45° (180°) 6 Pin DIN Socket 8 Pin DIN Socket |

MINIATURE JACK PLUGS & SOCKETS

MINIATURE INSULATED JACK PLUGS a range of miniature insulated jack plugs with strong plastic barrels and integral cable strain relief. Solder termination. Sold Individually.



| CODE | TYPE | PRICE |
|---------|----------------------------------|-------|
| 560-005 | 2.5mm Insulated Jack Plug Mono | £0.59 |
| 560-010 | 3.5mm Insulated Jack Plug Mono | £0.50 |
| 560-015 | 3.5mm Stereo Insulated Jack Plug | £0.60 |

2.5MM JACK PLUG AND SOCKET a 2.5mm jack plug and socket with soft plastic cover and cable protector. For cables up to 4mm diameter.

ter.

| CODE | TYPE | PRICE |
|---------|--------------------------|-------|
| 560-958 | 2.5mm Jack Plug Stereo | £0.79 |
| 560-960 | 2.5mm Jack Socket Stereo | £0.60 |

MINIATURE JACK SOCKETS a range of miniature enclosed jack sockets for 2.5 and 3.5mm jack plugs. Panel mounting, max panel thickness 2.5mm, panel cut out 4.5mm and 6mm for the 2.5 and 3.5mm sockets respectively. Solder

termination. Sold Individually.

| CODE | TYPE | PRICE |
|---------|-----------------------------------|-------|
| 560-060 | 2.5mm Enclosed Jack Socket | £0.35 |
| 560-065 | 3.5mm Enclosed Jack Socket | £0.40 |
| 560-075 | 3.5mm Stereo Enclosed Jack Socket | £0.49 |

JACK PLUGS & SOCKETS

STANDARD INSULATED JACK PLUGS a range of standard

insulated jack plugs with strong plastic barrels and integral cable strain relief. Solder termination. Sold Individually.



| CODE | TYPE | PRICE |
|---------|----------------------------------|-------|
| 560-035 | 6.3mm Insulated Jack Plug | £0.69 |
| 560-040 | 6.3mm Stereo Insulated Jack Plug | £0.79 |

OPEN CHASSIS STANDARD JACK SOCKET a standard open

type mono jack socket with unswitched contacts. Solder termination. Sold Individually.



| CODE | TYPE | PRICE |
|---------|--|-------|
| 560-432 | 6.3mm Mono Open Unswitched Jack Socket | £0.75 |

OPEN CHASSIS STANDARD JACK SOCKET a standard open type stereo jack socket with switched contacts. Available in stereo Solder termination.

Sold Individually.

| CODE | TYPE | PRICE |
|---------|--|-------|
| 560-434 | 6.3mm Stereo Open Switched Jack Socket | £0.90 |

PHONO PLUGS & SOCKETS

INSULATED PHONO PLUGS insulated phono plugs with plastic

covers in Red, Black. Sold Individually.

| CODE | TYPE | PRICE |
|---------|------------------|-------|
| 560-200 | Phono Plug Red | £0.45 |
| 560-205 | Phono Plug Black | £0.45 |

SINGLE CHASSIS PHONO SOCKETS chassis mounting phono sockets uninsulated type with plastic colour coded internal insulators for easy identification. Sold Individually.

| CODE | TYPE | PRICE |
|---------|---------------------------|--------------|
| 560-240 | Single Phono Socket Black | £0.50 |
| 560-245 | Single Phono Socket Red | £0.50 |

INSULATED PHONO LINE SOCKETS insulated cable mounting phono sockets. Available in Red or Black. Sold Individually.



| CODE | TYPE | PRICE |
|---------|-------------------------|-------|
| 560-270 | Red Phono Line Socket | £0.50 |
| 560-275 | Black Phono Line Socket | £0.50 |

DC POWER PLUGS & SOCKETS

DC POWER PLUGS a range of miniature power inlet plugs to suit a range of appliances. The standard plugs have 10mm shaft, long plugs have 14mm shaft. The size listed refers to the diameter of

the centre hole of the plug and outside diameter of the shaft.



| CODE | TYPE Hole dia | Shaft dia | PRICE |
|---------|---------------|----------------|-------|
| 560-355 | DC Plug 2.1mm | 5.5mm Standard | £0.60 |
| 560-360 | DC Plug 2.1mm | 5.5mm Long | £0.60 |
| 560-365 | DC Plug 2.5mm | 5.5mm Standard | £0.60 |
| 560-370 | DC Plug 2.5mm | 5.5mm Long | £0.60 |
| | | | |

DC POWER SOCKETS flush fitting, insulated DC power sockets with break contact to suit 2.1mm

and 2.5mm DC power plugs. Fixing centres 18mm.

| CODE | TYPE | PRICE |
|--------|-----------------------|-------|
| DCS021 | DC Power Socket 2.1mm | £0.79 |
| DCS025 | DC Power Socket 2.5mm | £0.79 |

DC POWER SOCKETS panel mounting DC power sockets in 2.1 and 2.5mm sizes mating with suitable DC power plugs. Integral single pole switch operates when plug is inserted or removed. Contacts rated at 1A 16V DC.

| CODE | TYPE | PRICE |
|---------|--------------------------|-------|
| 560-329 | 2.1mm Panel Power Socket | £1.55 |
| 560-330 | 2.5mm Panel Power Socket | £1.55 |

DC POWER LINE SOCKETS a range of rewireable miniature DC power line sockets to suit our range of DC power plugs. Available in 2.1mm and 2.5mm sizes and are supplied with integral cable strain relief.

| CODE | TYPE | PRICE |
|---------|----------------------------|-------|
| 560-450 | DC Power Line Socket 2.1mm | £1.65 |
| 560-455 | DC Power Line Socket 2.5mm | £1.65 |

RC PLUGS & SOCKETS

BULLET CONNECTORS 2mm a set of 2.0mm male and female

bullet connectors, supplied with heatshrink sleaving.



SHIELDED BULLET CONNECTORS 2.0mm a set of 2.0mm male

and female shielded bullet connectors, supplied with shrouds.

CODE **TYPE PRICE** 564-017 2.0mm Shielded Bullet Cons Male+Female Pair. £3.99 3.5mm Shielded Bullet Cons Male+Female Pair.. £3.99 4.0mm Shielded Bullet Cons Male+Female Pair.. £3.99 564-023

4mm BULLET MOTOR CONNECTORS a set of 4.0mm male and

female bullet connectors for motors. Supplied with heatshrink sleeve.

CODE **TYPE** PRICE 564-026 4.0mm Bullet Connector Set for Motors..... £3.99

LiPo MONITOR used to test the state of a 3 cell or 4 cell LiPo battery pack.

CODE 501-055 LiPo Battery Monitor for 3 Cells.....£10.99 LiPo Battery Monitor for 4 Cells......£10.99 500-056

LiPo RECEIVER PACK MONITOR used to test the state of a receiver monitior LiPo battery pack.

PRICE CODE **TYPE** 501-057 LiPo Receiver Pack Monitor......£11.99

R/C LEAD 4mm to Deans/Futaba/JST/2.1 JR/2.5 Futaba/extra

wire (pvc wire).

CODE **PRICE** 564-064 R/C Lead 4mm to Deans etc.....£10.65

R/C LEAD 4mm to Deans/Futaba/JST/2.1 JR/2.5 Futaba/2 croc

clips/extra wire (pvc wire).

CODE **TYPE PRICE** 564-065 R/C Lead 4mm to Deans etc.....£10.65 R/C LEAD 4mm to Deans/JST/Tamiya/Futaba/extra wire (18awg silicone).

CODE **TYPE PRICE** 564-066 R/C Lead 4mm to Deans etc.....£11.45

R/C LEAD 4mm to Deans/MPX/Tamiya/extra wire (16awg sili-

CODE **TYPE PRICE** 564-067 R/C Lead 4mm to Deans etc.....£11.45

R/C LEAD 4mm to Glow/Tamiya/Deans/JR/Futaba TX+RX PVC

CODE **TYPE PRICE** R/C Lead 4mm to Glow etc..... 564-068 £11.45

R/C LEAD DEANS EXTENSION CABLE an extension cable

Deans Male to Deans Female.

CODE **PRICE TYPE** 564-069 R/C Lead Deans Ext Cable Male - Female.......

R/C LEAD DEANS ADAPTOR CABLE an adaptor cable Deans

Male to Deans Male.

PRICE CODE 564-070 R/C Lead Deans Adpt Cable Deans Male - Male. £4.99

R/C LEAD ADAPTOR CABLE an adaptor cable Tamiya Female

to Deans Male.

CODE **PRICE** 564-071 R/C Ld Adt Cable Tamiya Female - Deans Male. £4.99

R/C LEAD ADAPTOR CABLE an adaptor cable Tamiya Male to

Deans Female.

CODE **TYPE** PRICE 564-072 R/C Ld Adt Cable Tamiya Male - Deans Female. £4.99

R/C LEAD ADAPTOR CABLE an adaptor cable Deans Male to

Micro Tamiya Female.

JR CONNECTOR a male and female set of JR connectors.

CODE **TYPE PRICE** 564-073 R/C Adt Cable Deans Male - Micro Tam Female. £4.99

R/C LEAD ADAPTOR CABLE an adaptor cable Deans Female to

Micro Tamiva Male

CODE **TYPE** PRICE 564-074 R/C Adt Cable Deans Female - Micro Tam Male. £4.99

R/C LEAD ADAPTOR CABLE an adaptor cable Tamiya female to Micro Tamiya male Adaptor.

CODE **PRICE** R/C Adt Cable Tamiya XXX- Micro Tamiya XXX. £4.99 564-075

R/C LEAD ADAPTOR CABLE an adaptor lead Battery Plug Male to Tamiya Female. Length XXX

CODE **PRICE TYPE** 564-076 R/C Adapt Battery Plug Male - Tamiya Female.... £3.29

R/C LEAD ADAPTOR CABLE an adaptor lead Battery Plug Female to Tamiya Male.

CODE **PRICE** 564-077 R/C Adapt Battery Plug Female - Tamiya Male.... £3.29

R/C LEAD ADAPTOR CABLE an adaptor lead JST Female to Tamiya.

CODE PRICE 564-078 R/C Adapt JST Female - Tamiya...... £4.10

R/C LEAD ADAPTOR CABLE an adaptor lead Glow to Tamiya Charger Cable.

CODE 564-079 R/C Adaptor Lead Glow - Tamiya Charger Cable £4.90

> FREE PARKING FOR 2 HOURS **OUTSIDE OF OUR SHOP**

CODE **TYPE PRICE** R/C JR Connectors Male/Female Set.......£2.49 564-038

FUTABA CONNECTOR a male and female set of Futaba connec-

TYPE PRICE CODE R/C Futaba Connectors Male/Female Set............ £2.49 564-039

JST/BEC CONNECTOR a male and female set of JST/BEC connectors.

CODE **TYPE** PRICE 564-040 R/C JST/BEC Connectors Male/Female Set....... £2.49

MICRO DEANS STYLE CONNECTOR a male and female set of Micro Deans Style connectors.

CODE PRICE **TYPE** 564-036 Micro Deans Style Connectors Male/Female Set. £3.29

SILICONE WIRE coils of heat resistant silicone wire in, sizes and length as listed.

| CODE | TYPE | PRICE |
|---------|-------------------------------|-------|
| 522-105 | Silicone Wire 10 Awg 1M Red | £2.99 |
| 522-106 | Silicone Wire 10 Awg 1M Black | £2.99 |
| 522-103 | Silicone Wire 12 Awg 1M Red | £2.99 |
| 522-104 | Silicone Wire 12 Awg 1M Black | £2.99 |
| 520-001 | Silicone Wire 14 Awg 1M Red | £2.49 |
| 520-002 | Silicone Wire 14 Awg 1M Black | £2.49 |
| 520-004 | Silicone Wire 14 Awg 1M Blue | £2.49 |
| 522-101 | Silicone Wire 16 Awg 1M Red | £2.49 |
| 522-102 | Silicone Wire 16 Awg 1M Black | £2.49 |
| 522-099 | Silicone Wire 18 Awg 1M Red | £2.49 |
| 522-100 | Silicone Wire 18 Awg 1M Black | £2.49 |
| 522-097 | Silicone Wire 20 Awg 1M Red | £3.25 |
| 522-098 | Silicone Wire 20 Awg 1M Black | £3.25 |

R/C LEAD FUTABA Y-LEADS a Futaba Y Lead available in 30cm and 60cm lengths.

| CODE | TYPE | PRICE |
|---------|-----------------------------|-------|
| 564-041 | R/C Lead Futaba Y-Lead 30cm | £4.90 |
| 564-042 | R/C Lead Futaba Y-Lead 60cm | £6.55 |

R/C LEAD JR Y-LEADS a JR Y Lead available in 30cm and 60cm lengths.

| CODE | TYPE | PRICE |
|---------|-----------------------------|-------|
| 564-043 | R/C Lead Futaba Y-Lead 30cm | £4.90 |
| 564-044 | R/C Lead Futaba Y-Lead 60cm | £6.55 |

TRAXXAS STYLE CONNECTORS a sets of male and female

Traxxas style connectors.

CODETYPEPRICE564-300RC Connector Traxxas Style Male/Female Set....£4.10564-031RC Connector Traxxas Style Male Pair......£4.10564-032RC Connector Traxxas Style Female Pair.....£4.10

R/C CONNECTOR a Female Micro Tamiya connector with 10cm 18AWG wires.

CODE TYPE PRICE 564-080 R/C Conn Micro Tamiya Female + 18AWG Wire. £4.99

R/C CONNECTOR a Male Micro Tamiya connector with 10cm 18AWG silicone wires.

CODE TYPE PRICE 564-081 R/C Conn Micro Tamiya Male + 18AWG Wires... £3.29

R/C CONNECTOR GOLD PLATED BATTERY BARS a set of 8 battery bars, gold plated.

Length 22mm.

CODE TYPE PRICE

564-082 R/C Connectors Gold Plated Battery Bars 8Pack £7.39

R/C CONNECTOR DEANS PLUGS a packs Deans Plugs with

heatshrink sleave. Supplied in packs of 2 and 10..

R/C FEMALE BLACK CONNECTOR a female Black connector 2

pin, with 10cm 20AWG silicone wire.

CODE TYPE PRICE 564-084 R/C Female Black Connect 2 Pin + 22AWG Wire £4.09

R/C MALE BLACK CONNECTOR a male Black connector 2 pin, with 10cm 20AWG silicone wire.

CODE TYPE PRICE

564-085 R/C Male Black Connect 2 Pin + 22AWG Wire.... £4.09

R/C FEMALE WHITE CONNECTOR a female white connector 2 pin, with 10cm 20AWG silicone wire.

CODE564-085

TYPE
PRICE
PRICE
PRICE
PRICE
PRICE
PRICE
PRICE
PRICE

R/C MALE WHITE CONNECTOR a male white connector 2 pin, with 10cm 20AWG silicone wire.

CODE TYPE PRICE 564-087 R/C Male White Connect 2 Pin + 22AWG Wire.... £4.09

R/C BANANA CHARGING LEAD a Deans style charging lead with 4mm banana plugs.

Length 10cm.

CODE564-058

R/C Banana Charging Lead 4mm Plugs - Deans. £6.59

R/C LEAD Y-HARNESS a Deans style Y-Harness for saddle packs.

CODE TYPE PRICE 564-060 R/C Lead Deans Style Y-Harness for Saddle Pks £8.15

R/C BANANA CHARGING LEAD a Deans style charging lead with 4mm banana plugs.
Length 10cm.

CODE TYPE PRICE 564-058 R/C Banana Charging Lead 4mm Plugs - Deans. £6.59

GOLD PLATED BULLET CONNECTORS bulk packs of 25 male and 25 female bullet connectors in a range of sizes.

 CODE
 TYPE
 PRICE

 564-107
 G/P Bullet Connectors M+F 2mm Pack of 25......£21.99

 564-108
 G/P Bullet Connectors M & F 3mm Pack of 25.... £21.99

 564-109
 G/P Bullet Connectors M & F 3.5mm Pack of 25... £21.99

 564-110
 G/P Bullet Connectors M & F 4mm Pack of 25.... £21.99

7.2V PLUG & SOCKET an un-assembled 7.2V plug and socket for connecting battery packs.

7.2V PLUG & SOCKET WITH LEADS an assembled 7.2V plug and socket for connecting to battery packs. Lead length 240mm approx (both male and female).

MAINS POWER CORD SETS

IEC CHASSIS MAINS INLET PLUG panel mounting IEC mains inlet connectors approved to IEC320 and CEE22. Available with either 4.8mm or 6.3mm fast-on connections. Used for connecting mains power to equipment. Contact

rating 10A 250V AC. A rear insulating boot is available Code 560-520.



IEC CHASSIS SOCKET a female version of chassis plug used for power take off applications. Terminated with 4.8mm fast-on connections. Contact rating 10A 250V AC.

This connector has all major approvals. A rear insulating boot is available Code 560-520.

TYPF PRICE CODE

INSULATING BOOTS a range of insulating boots to ensure safe connections to rear of IEC chassis plugs and sockets. Code No 560-520 suits IEC unfused sockets 560-475 & 560-480. Part No 560-525 suits IFC fused sockets

560-490 & 560-495, also IEC chassis socket Part No. 560-500



IEC CABLE SOCKET a rewireable cable socket manufactured to CEE22 and BS4491 approvals. Terminated with internal screw connections and cable strain relief.

Contact rating 6A 250V AC.

TYPE CODE **PRICE**

REWIREABLE CABLE PLUG A CEE22/BS4491 straight rewirable power take-off connector. Fitted with internal screw connections, screw grip cable clamp and strain relief. Contact rating 10A 250V AC.

PRICE CODE 560-418 Rewireable IEC Plug......£1.99

IEC/CEE22 CORD SET An IEC/CEE22 cord set, comprising a free straight socket and shrouded power take-off plug moulded to a 1.99 metre length of 3 core 0.75m2 cable sheathed overall in

black. Designed primarily for power interconnection between equipment. Rated 6A 250V AC Cable Approved to BS6500.



| CODE | TYPE | PRICE |
|---------|-------------------------------|-------|
| 560-420 | IEC Plug & Socket Cord Set 2m | £3.99 |

13A FUSED PLUG TO STRAIGHT IEC MAINS CORD a non rewireable straight socket and moulded 13A plug fused at 5A moulded to a length of 3 core 0.75mm cable sheathed overall in black. Manufactured and

ASTA approved to BS1363/A. Cable approved to BS6500.



MOULDED 13A FUSED PLUG AND MAINS CORD a non rewireable moulded 13A plug fused at 5A moulded to a length of 3 core 0.75mm cable sheathed overall in black. Fully Tested and by

ASTA The free cable end has stripped conductors. Cable Length 1.99 metres.

CODE

CODE



MOULDED 13A FUSED PLUG TO FIGURE 8 CONNECTOR a non rewireable moulded 13A plug fused at 3A moulded to a length of 2 core 0.75mm cable sheathed overall in black. The 8.6mm cen-

tred 2 pin socket is ideal for use with portable battery/mains equipment. Cable Length 1.5m.




| CODE | TYPE | PRICE |
|---------|-------------------------------------|-------|
| 560-560 | 13A Plug to Figure 8 Connector 1.5M | £3.99 |

D PLUGS & SOCKETS

'D' CONNECTORS standard D series connectors in 9 to 50 way with solder bucket terminals,

which may be in-line or panel mounted. Covers listed below. Rating (each pin) 5A.



CON420 CON430 25 Way D Socket.......£0.85 CON440 37 Way D Plug...... £3.75 CON470 50 Way D Skt.....(Available While Stocks Last). £0.90

'D' CONNECTOR COVERS two part 'D' connector covers moulded

in ABS, supplied complete with cable clamp and short jack screws. Top cable entry type. (Fits both male or female D connectors).



| ÈΕ |
|----|
| 50 |
| 55 |
| 65 |
| 99 |
| |

CIGAR LIGHTER PLUGS & SOCKETS

CAR DC POWER PLUG STANDARD used for taking power from a car cigar lighter socket. Standard quality, unfused version. Maximum continuous rating 3A 12V.


CAR DC POWER PLUG HIGH QUALITY used for taking power from a car cigar lighter socket. A superior quality version with spring loaded contacts and rubber cable protector. Unfused version. Maximum continuous

rating 3A 12V.

| CODE | TYPE | PRICE |
|---------|--------------------------------|-------|
| 562-026 | Car DC Power Plug High Quality | £0.90 |

CAR DC POWER PLUG FUSED a superior quality car cigar

lighter plug with 5A fuse. It has spring loaded contacts a rubber cable protector.



IN LINE CAR CIGAR LIGHTER SOCKET an in-line car cigar

lighter socket, 12Vdc, with brass contacts and rubber cable protector. Solder tags for cable fixing.



CIGAR LIGHTER ADAPTORS

CIGAR LIGHTER SOCKET SPLITTER an in car adaptor to pro-

vide two cigar lighter sockets from the single socket normally provided in the car. internally fused at 15A.



| CODE | TYPE | PRICE |
|---------|-------------------------------|-------|
| 563-195 | Cigar Lighter Socket Splitter | £4.5 |

CIGAR LIGHTER SOCKET EXTENSION a 2 way adaptor to give 2 x 12vdc car cigar lighter sockets from one socket. Incorporates

a power on LED protective caps and fuse. 1 plug to 2 sockets.



CODE TYPE PRICE 563-032 Cigar Lighter Socket Extension 1 Plug to 2 Skts... £5.99

POWER LEAD provides a cigar lighter socket where none is fitted

or where one is required outside of the car. Heavy duty crocodile clips take power directly from battery. Max current 10A. Length 600mm.



POWER LEAD a cigar lighter plug with lead terminating in a 4-way adaptor to give 4 alternative plugs:- 2.5mm and 3.5mm jack plugs, 2.1mm and 2.5mm DC plugs. Max current 2A. Fuse (2A) built into the plug. Length 1.8m.



EXTENSION LEAD a lead to extend cigar lighter-type socket to a distance of 2m. Max current 5A. Fuse (5A) built into the plug.



CODE TYPE PRICE 563-275 Extension Lead Cigar Plug to Cigar Socket 2M... £4.35

PIN STRIPS & SOCKETS

TURNED PIN S I L HEADER Single In Line headers with tin plated turned brass pins, designed to be snapped off to the desired length for use as headers for PCB interconnection or miniature plugs and sockets when used in conjunction with S I L Sockets. Available in 20 or 32 way strips with

pins at 0.1" centres.

| CODE | TYPE | PRICE |
|---------|-----------------------|-------|
| 561-000 | PCB SIL Header 20 Way | £1.90 |
| 561-005 | PCB SIL Header 32 Way | £2.99 |

TURNED PIN S I L SOCKETS Single In Line low profile sockets with high quality machined contacts. Moulded in black glass-filled flame retardant polyester. Temperature range -55°C to 180°C. Can be snapped off to the desired length for use as sockets for PCB interconnection or miniature plugs and sockets when used in conjunction with S I L Headers. Available in 20 or 32 way strips with pins at 0.1" centres.

| CODE | TYPE | PRICE |
|---------|------------------------|-------|
| 561-010 | PCB SIL Sockets 20 Way | £0.70 |
| 561-015 | PCB SIL Sockets 32 Way | £0.95 |

TAG STRIPS

MINIATURE TAG STRIP with 28 hot tinned insulated tags mounted on a paxolin strip. Dims:- 194mm x 16.7mm x 4mm.

| 0.0.0.0.0 | | 0000000000000000 |
|------------------------|---------------------|---|
| IIII ay ay ay ay ay ay | -VOTOVOVOVOVAUALOR: | To Ro |
| | | |
| | | 0 |


| CODE | TYPE | PRICE |
|--------|---------------------|-------|
| TAS035 | Miniature Tag Strip | £2.25 |

TAG STRIP 28 hot tinned tags mounted on a paxolin strip which may be cut if required, of the 28 tags 18 are insulated and 10 are earth points right-angled for fixing. Fixing centres 28.56mm x 4mm, Dims:- 266 x 18 x 10mm.

विद्यार्थित स्ट्रांस्टर्श स्ट्रांस्टर्श स्ट्रांस्टर्श स्ट्रांस्टर्श स्ट्रांस्टर्श स्ट्रांस्टर्श स्ट्रांस्टर्श

| CODE | TYPE | PRICE |
|--------|-------------------|-------|
| TAS040 | Tag Strip 28 Tags | £2.90 |

TAG BOARD miniature SRBP bases with hot-tinned tags for easy soldering. 36 tags in 2 rows of 18. Dims:- L117 x W38 x H7.5mm.



| CODE | TYPE | PRICE |
|--------|-------------------|-------|
| TAB051 | Tag Board 36 Tags | £2.99 |

TERMINAL BLOCKS

TERMINAL BLOCKS 12 way flexible terminal block strips that are

easily cut into shorter lengths. 3, 5, 10, 15 and 30A.



| CODE | TYPE | PRICE |
|---------|------------------------------|-------|
| TB0010 | Terminal Block 3A | £0.50 |
| 560-111 | Terminal Block 3A Pack of 10 | £4.50 |
| TB0020 | Terminal Block 5A | £0.69 |
| 560-112 | Terminal Block 5A Pack of 10 | £5.99 |
| 560-890 | Terminal Block 10A | £1.20 |
| TB0030 | Terminal Block 15A | £1.49 |
| 560-892 | Terminal Block 30A | £1.99 |

PLUG-IN TERMINAL BLOCKS

PLUG-IN TERMINAL BLOCKS a range of pluggable industrial quality terminal strips moulded in self extinguishing polypropylene. They are supplied as 12 way blocks which may be cut down to size. The wires are connected by a screw fixing. Supplied as a pair of male and female strips. The blocks are robust and ideal for joining wires that require to be moved frequently. Available with 3

connector pitches 8mm rated at 6A, 10mm and 12mm pitches are both rated at 10A.



| CODE | TYPE | PRICE |
|---------|---|-------|
| 560-843 | Plug-in Terminal Block M/F - 6A/8mm Pitch | £3.99 |
| TB0025 | Plug-in Terminal Block M/F - 10A/10mm Pitch | £4.50 |
| 560-498 | Plug-in Terminal Block M/F - 16A/12mm Pitch | £6.89 |
| | | |

SOLDER TAGS

SOLDER TAGS hot tinned brass tags to suit both metric and BA screw sizes. Supplied in packs of 25.

| CODE | TYPE | PRICE |
|--------|----------------------|-------|
| TAG-M6 | Solder Tags M6/OBA | £1.35 |
| TAG-M5 | Solder Tags M5/2BA | £1.35 |
| TAG-M4 | Solder Tags M4/3BA | £1.35 |
| TAGM35 | Solder Tags M3.5/4BA | £1.35 |
| TAG-M3 | Solder Tags M3/6BA | £1.35 |
| TAG-M2 | Solder Tags M2/8BA | £1.35 |

CROCODILE CLIPS

STANDARD CROCODILE CLIPS nickel plated steel, length 45mm, will accept 4mm plugs.

| CODE | TYPE | PRICE | |
|--------|----------------------------|-------|--|
| CON010 | Crocodile Clips 42mm, Pair | £0.45 | |

MINIATURE CROCODILE CLIPS a range of miniature insulated crocodile clips. Solder termination with cable grip. Length 33mm, 6 colours:- Black(**BK**), Blue(**BU**), Green(**GN**), Red(**RD**), White(**WH**) and Yellow(**YL**). Price is EACH order by CODE, COLOUR + QUANTITY.


CODE TYPE PRICE
CON020 Mini Croc Clip (COLOURS + QUANTITY) EACH. £0.25

CROCODILE LEAD PACK a set of ten leads, 18 inches long in

five assorted colours. Terminated at each end with an insulated miniature crocodile clip. Ideal for use as test leads and project work.

| CODE | TYPE | PRICE |
|--------|---------------------|--------------|
| CON030 | Crocodile Lead Pack | £3.99 |

HEAVY DUTY CROCODILE LEAD PACK a set of five leads 18" long in five assorted colours. Terminated at each end with an insulated crocodile clip. 55/0.1mm test lead cable is used, 2A max. Ideal for use as test leads.



MINIATURE PLUGS & SOCKETS

2mm PLUGS & SOCKETS with tough plastic covers, rated 3A, solder connection. Panel mounting socket. 5.8mm fixing hole.

| CODE | TYPE | PRICE |
|--------|------------------|-------|
| CON080 | 2mm Plug Red | £0.45 |
| CON090 | 2mm Plug Black | £0.45 |
| CON100 | 2mm Socket Red | £0.50 |
| CON110 | 2mm Socket Black | £0.50 |

4mm PLUGS & SOCKETS a range of solder connection 4mm plugs and sockets, the plugs may also be used in conjunction with 4mm terminal posts.

| | (Car | |
|--------|------------------|-------|
| CODE | TYPE | PRICE |
| CON160 | 4mm Plug Red | £0.65 |
| CON170 | 4mm Plug Black | £0.65 |
| CON180 | 4mm Socket Red | £0.45 |
| CON190 | 4mm Socket Black | £0.45 |

FUSES & FUSE HOLDERS

MAINS FUSES 1 inch mains fuses for use in 13A plugs. Conforming to BS1362. ASTA certified.

| CODE | TYPE | PRICE |
|--------|----------------|-------|
| MF001A | Mains Fuse 1A | £0.32 |
| MF002A | Mains Fuse 2A | £0.32 |
| MF003A | Mains Fuse 3A | £0.29 |
| MF005A | Mains Fuse 5A | £0.29 |
| MF007A | Mains Fuse 7A | £0.29 |
| MF010A | Mains Fuse 10A | £0.29 |
| MF013A | Mains Fuse 13A | £0.29 |

QUICK BLOW FUSES 20 x 5mm a range of quick blow glass fuses manufactured to IEC127 sheet 2. Rated 250V ac. Sold individually.

| CODE | TYPE | PRICE |
|---------|-----------------------|-------|
| 580-345 | Quick Blow Fuse 200mA | £0.29 |
| QBF110 | Quick Blow Fuse 250mA | £0.29 |
| 580-347 | Quick Blow Fuse 315mA | £0.29 |
| 580-950 | Quick Blow Fuse 400mA | £0.2 |
| QBF115 | Quick Blow Fuse 500mA | £0.29 |
| 580-349 | Quick Blow Fuse 630mA | £0.29 |
| 580-350 | Quick Blow Fuse 800mA | £0.29 |
| QBF120 | Quick Blow Fuse 1A | £0.29 |
| 580-351 | Quick Blow Fuse 1.25A | £0.29 |
| QBF125 | Quick Blow Fuse 1.6A | £0.29 |
| QBF130 | Quick Blow Fuse 2A | £0.29 |
| 580-952 | Quick Blow Fuse 2.5A | £0.28 |
| QBF135 | Quick Blow Fuse 3.15A | £0.29 |
| QBF140 | Quick Blow Fuse 4A | £0.29 |
| QBF150 | Quick Blow Fuse 5A | £0.29 |

CHASSIS MOUNTING 20MM FUSEHOLDER a chassis mounting

fuse holder to suit 20 x 5mm fuses up to a 6.3A rating 250V ac. Moulded in a flame retardant material with tinned nickel plated brass.



15A CHASSIS MOUNTING 20MM FUSEHOLDER a chassis

mounting fuseholder to suit 20x5mm fuses with single hole fixing and anti-rotation spigot. Terminated by 4.8mm faston terminals.

| CODE | TYPE | PRICE |
|---------|--------------------------------------|-------|
| 580-378 | 15A Chassis Mounting 20mm Fuseholder | £1.05 |

FINGER RELEASE 20MM FUSEHOLDER a panel mounting finger release fuseholder with knurled cap, moulded in black self extinguishing polycarbonate. A screwdriver/coin slot is incorporated in the cap. Max fuse rating 6.3A 250V ac.

| CODE | TYPE | PRICE |
|--------|--------------------------------|--------------|
| FHFR10 | 20mm Finger Release Fuseholder | £0.89 |

IN LINE FUSEHOLDER 5 X 20MM an in line fuse holder for holding 5×20 mm. Plastic housing with bayonet fixing. Fitted with an 18cm wire.

| CODE | TYPE | PRICE |
|---------|-----------------------------|-------|
| 580-986 | In Line Fuseholder 5 x 20mm | £0.79 |

AUTOMOTIVE FUSES a range of quick blow blade type fuses designed primarily for use in automotive applications and becom-

ing common in portable equipment. Rated 32V dc with a breaking capacity of 1000A. Colour coded for easy identification.

| CODE | TYPE | Colour | PRICE |
|---------|----------------------|--------|-------|
| AF2300 | Automotive Fuse 3A | Violet | £0.25 |
| AF2305 | Automotive Fuse 5A | Tan | £0.25 |
| AF2310 | Automotive Fuse 7.5A | Brown | £0.25 |
| AF2315 | Automotive Fuse 10A | Red | £0.25 |
| AF2320 | Automotive Fuse 15A | Blue | £0.25 |
| AF2325 | Automotive Fuse 20A | Yellow | £0.25 |
| AF2330 | Automotive Fuse 25A | Clear | £0.25 |
| AF2335 | Automotive Fuse 30A | Green | £0.25 |
| 580-982 | Automotive Fuse 40A | Red | £0.25 |
| | | | |

FUSE SPLICES an in-line fuseholder for use with automotive type fuses. The holder is placed over the cable and then crimped with pliers.

| CODE | TYPE | Wire Size | PRICE |
|--------|----------------------------|-----------|--------------|
| CC0195 | In-line Fuse Holder Single | 1.0-2.0 | £0.90 |

CAR FUSE HOLDER a plastic fuse holder with cover for blade type car fuses.

| CODE | TYPE | PRICE |
|---------|-----------------|--------------|
| 580-988 | Car Fuse Holder | £1.49 |

20A IN-LINE AUTOMOTIVE FUSEHOLDER WITH LED An inline automotive fuseholder incorportating a two part PVC assembly with safety strap. Current rating 20A 12V-24V DC. LED on fuseholder lights to show fuse is good. Suitable for standard quick blow blade type fuses. Access to the fuse is by means of a snap-fit lid on top of the holder. Damp proof and water proof. Supplied with 110mm of 14AWG red

insulated wire each side of fuseholder. Dim 46(L) x 35mm (W).

| CODE | TYPE | PRICE |
|---------|--|--------------|
| 14-0136 | 20A In-line Automotive Fuseholder With LED | £1.99 |

THERMAL CIRCUIT BREAKERS

THERMAL PCB MOUNTING CIRCUIT BREAKERS a range of miniature auto-resetting circuit breakers suitable for protecting equipment against over-current conditions, eg audio speakers, amplifiers, power supplies etc. Moulded in phenolic resin with PCB pins on a 7.5mm pitch. Dims 22 x 12.6 x 6mm. Rated at 250V ac. Supplied individually.

Technical Specification Max Trip time


| Current rating 1.0A 1.6A 2.2A 3.0A 5.0A | Interrupt current 20A 20A 20A 30A 50A | overload 200% <30s <30s <30s <30s <30s | current 300% <5s <5s <5s <5s | Internal resistance <150m <100m <75m <35m <30m | NA - 101 | |
|---|---|--|---|--|----------|-------|
| CODE | TYPE | | | | 0.00 | PRICE |
| 580-200 | Thermal F | PCB Circui | t Breaker 1 | 1A | | £2.85 |
| 580-205 | Thermal F | PCB Circui | t Breaker 1 | 1.6A | | £2.85 |
| 580-210 | Thermal F | PCB Circui | t Breaker 2 | 2.2A | | £2.85 |
| 580-215 | Thermal F | PCB Circui | t Breaker 3 | 3A | | £2.85 |

Thermal PCB Circuit Breaker 5A......£2.85

580-220

LED's

SUB-MINIATURE 1.8mm AXIAL LED. A range of miniature axial LEDs in a water clear package suitable for high density PCB applications. Cathode is identified by a stripe on one lead. Sold individually or in packs of 100.



| CODE | TYPE | PRICE |
|--------|---------------------------------|-------|
| LED011 | Sub-Mini Axial 1.8mm LED Red | £0.25 |
| LED021 | Sub-Mini Axial 1.8mm LED Green | £0.25 |
| LED031 | Sub-Mini Axial 1.8mm LED Yellow | £0.25 |

MINIATURE 1.8mm LED. A range of miniature LEDs in a diffused package of 1.8mm dia, suited to through panel applications. The cathode is identified by the shorter lead.

| | | 5 | | | | | |
|---------|-------------|--------|--------|------|------------|-------|---------|
| | lF | VF | VF | VR | Int.at IF | View | Wave |
| | max. | typ. | max. | max. | mcd. | angle | length |
| Red | 20mA | 2V | 2.5V | 5V | 2.0 @ 10mA | 30° | 660 |
| Green | 30mA | 2.2V | 2.5V | 5V | 5.0 @ 10mA | 30° | 565 |
| Yellow | 30mA | 2.1V | 2.5V | 5V | 5.0 @ 10mA | 30° | 590 |
| White | 30mA | 3.4V | 4.0V | 5V | 4200@10mA | 30° | 590 |
| CODE | TYPE | | | | | | PRICE |
| LED040 | Mini 1. | .8mm L | ED Red | b | | | £0.25 |
| LED050 | Mini 1. | .8mm L | ED Gre | en | | | £0.25 |
| LED060 | Mini 1. | .8mm L | ED Yel | low | | | £0.25 |
| 620-850 | Mini 1. | .8mm L | ED Wh | ite | | | . £0.50 |

MINIATURE 3mm LED. A range of miniature 3mm round LEDs housed in a diffused coloured package. The cathode is identified by a flat on the body. Sold Individually or in packs of 100.

| | lF | VF | VF | VR | Int.at IF | View | Wave |
|------------------|----------------------------|-------------------------|--------|----------|------------|-------|-------------------------|
| | max. | typ. | max. | max. | mcd. | angle | length |
| Red | 20mA | 2V | 2.5V | 5V | 3.2 @ 10mA | 120° | 660 |
| Green | 30mA | 2.2V | 2.5V | 5V | 20 @ 10mA | 120° | 565 |
| Yellow | 30mA | 2.1V | 2.5V | 5V | 20 @ 10mA | 120° | 590 |
| | | | | | | | |
| | | | | | | | |
| CODE | TYPE | | | | | | PRICE |
| LED070 | – | | D Red | | | | |
| | Mini 3 | mm LE | | | | | £0.20 |
| LED070 | Mini 3 Mini 3 | mm LE | D Gree | en | | | £0.20 £0.20 |
| LED070 LED080 | Mini 3 Mini 3 Mini 3 | mm LE mm LE mm LE | D Gree | en ow | | | £0.20 £0.20 £0.20 |

3mm BLUE LED. A high intensity blue LED with a 430nm peak wavelength with intensity of 40mcd in a standard 3mm diffused blue package.

| and paramaga | | | - | | THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN COLUMN TW | | |
|---------------|------------------------|------------|------------------------|------------------------|--|------------|-------|
| | I _F max. | VF typ. | V _F max. | V _R max. | Int.at IF mcd. | View angle | |
| Diffused Blue | 30mA | 4.5V | 5.5V | 5V | 40 @ 20mA | 60° | |
| CODE TY | /PE | | | | | | PRICE |
| LED1460 Hi | gh Inte | nsity 3 | mm Dif | fused B | lue LED | | £1.49 |
| | | | | | | | |

3MM WHITE LEDs 3mm white LEDs housed in a water clear package. Int.at 20mA Chromaticity View max max mcd. angle Kingbright White X=0.30,Y=0.30 Nichia White X=0.31,Y=0.32 4.3V 5.0V 600 35°C 900 5.0V CODE PRICE 622-122 3mm LED White Kingbright..... 622-120 3mm LED White Nichia......£3.50 **5 and 12V 3mm LED.** A range of 3mm LEDs incorporating an inbuilt series resistor enabling the LED to be directly connected to 5 or 12V supply lines. All devices are intensity and colour matched. Cathode identified by shorter lead. Sold Individually or in packs of 100.

| | l⊧ max. | VF typ. | V _R max. | Ptot mW _(max.) | Int at IF mcd. | View angle | Wave length |
|------------|------------|------------|------------------------|------------------------------|----------------|---------------|----------------|
| 5V HE Red | 150mA | ,, | 5V | 310 | 80 @ 10mA | 120° | 630 |
| 5V Green | 150mA | 8V | 5V | 310 | 32 @ 10mA | 120° | 565 |
| 5V Yellow | 150mA | 8V | 5V | 310 | 32 @ 10mA | 120° | 590 |
| 12V HE Red | 150mA | 15V | 5V | 310 | 80 @ 10mA | 120° | 630 |
| 12V Green | 150mA | 15V | 5V | 310 | 32 @ 10mA | 120° | 565 |
| 12V Yellow | 150mA | 15V | 5V | 310 | 32 @ 10mA | 120° | 590 |
| CODE | TVDE | | | | | | DDIC |

| CODE | TYPE | PRICE |
|---------|--------------------|-------|
| LED150 | 3mm 5V LED HE Red | £0.35 |
| LED160 | 3mm 5V LED Green | £0.35 |
| LED170 | 3mm 5V LED Yellow | £0.35 |
| LED180 | 3mm 12V LED HE Red | £0.35 |
| LED190 | 3mm 12V LED Green | £0.35 |
| LED200 | 3mm 12V LED Yellow | £0.35 |
| 17-1909 | 3mm 12V LED White | £1.75 |
| | | |

3mm BI-COLOUR LED. A range of miniature bi-colour LEDs offering several colour options housed in a milky white diffused package.

| | lF | VF | VF | VR | Int.at IF | View | Wave | | | |
|--------|-------|-------|-------|------|-----------|-------|--------|--|--|--|
| | max. | typ. | max. | max. | mcd. | angle | length | | | |
| Red | 30mA | 2V | 2.5V | 5V | 40 @ 20mA | 60° | 625 | | | |
| Green | 30mA | 2.2V | 2.5V | 5V | 40 @ 20mA | 60° | 565 | | | |
| Vollow | 30m / | 2 11/ | 2.5\/ | 5\/ | 40 @ 20mA | en° | 500 | | | |

| CODE | TYPE | PRICE |
|--------|------------------------------|--------------|
| LED240 | 3mm Bi-colour LED Red/Green | £0.50 |
| LED250 | 3mm Bi-colour LED Red/Yellow | £0.50 |

3mm TRI-COLOUR LED a miniature tri-colour LED offering several colour options housed in a milky white package. Uses a common cathode configuration and will display red, green or yellow when both diodes are connected together.

| | - | | | | | | |
|--------------|------------------------|------------------------|---------------------|------------------------|------------------------|------------|----------------|
| | I _F max. | V _F typ. | V _F max. | V _R max. | Int.at IF mcd. | View angle | Wave length |
| Red Green | 25mA 25mA | 2V 2.2V | 2.5V 2.5V | 5V 5V | 50 @ 20mA 50 @ 20mA | 60° 60° | 625 565 |

| CODE | TYPE | PRICE |
|--------|------------------------------|-------|
| LED265 | 3mm Tri-colour LED Red/Green | £0.50 |

STANDARD 5mm LED. A range of small LEDs suitable for PCB and panel mounting applications. 5mm diameter. Cathode identified by a flat on the body. Sold individually or in packs of 100.

| | | | | _ | | | |
|--------|------------------------|------------------------|------------------------|------------------------|-------------------|---------------|----------------|
| | l _F max. | V _F typ. | V _F max. | V _R max. | Int.at IF mcd. | View angle | Wave length |
| Red | 20mA | 1.7V | 2V | 5V | 3.2 @ 10mA | 60° | 625 |
| Green | 25mA | 2.2V | 2.5V | 5V | 32 @ 10mA | 60° | 565 |
| Yellow | 30mA | 2.1V | 2.5V | 5V | 32 @ 10mA | 60° | 590 |

| CODE | TYPE | PRICE |
|--------|------------------------------------|-------|
| LED270 | Standard 5mm LED Red | £0.20 |
| LED280 | Standard 5mm LED Green | £0.20 |
| LED290 | Standard 5mm LED Yellow | £0.20 |
| LED300 | ANY MIX OF 6 OF THE ABOVE 5mm LEDs | £1.00 |

IF THERE ARE OTHER PRODUCTS THAT YOU WOULD LIKE US TO STOCK, PLEASE FEEL FREE TO LET US KNOW

5mm BLUE LED a high intensity blue LED with a 430nm peak wavelength and intensity of 50mcd. The device is in a standard 5mm package.

| | | | | - | | | | |
|----------|-------|------------|-----------|--------|-----------|-------------|-------|-------|
| | | lF | | | | | | |
| VF | VF | VR | Int.at IF | | View | | | |
| | | max. | typ. | max. | max. | mcd. | angle | |
| Diffused | Blue | 30mA | 4.5V | 5.5V | 5V | 50@20 mA | 50° | |
| Water C | lear | 25mA | | 4.2V | 5V | 1200@20 mA | 15° | |
| CODE | . 1 | ΓΥΡΕ | | | | | | PRICE |
| LED14 | 180 F | High Inter | nsity 5m | ım Dit | ffused B | lue LED | | £0.95 |
| 622-86 | 32 F | High Inter | nsity 5m | ım Wa | ater Clea | ar Blue LED | | £0.95 |

5MM WHITE LED A range of 5mm high intensity white LED's from Nichia, Kingbright and TruOpto . Housed in water clear packages the devices are suited to a wide range of applications and can be used as direct replacements for filament lamps.

| | | | Talentin-U | | | |
|-------------|-------------|------------------------|---------------|-----------|---------------|-------|
| | V⊧ max. | V _R max. | Chromaticity | Int.@20mA | View angle | |
| Nic 1100mcd | | | X=0.31,Y=0.32 | 1100 | 50° | |
| KB 3200mcd | 4.0V | 5.0V | X=0.34,Y=0.35 | 3200 | 20° | |
| TO 3000mcd | 4.2V | 5.0V | X=0.31,Y=0.32 | 3000 | 15° | |
| CODE | TYPE | | | | | PRICE |
| 622-145 | Kingbr | ight 5m | m White LED | 300mcd | | £1.25 |
| 622-147 | Kingbr | ight 5m | m White LED | 3200mcd | | £1.75 |
| 622-860 | TruOp | to 5mm | White LED 30 | 000mcd | | £0.90 |
| | | | | | | |

5mm BI-COLOUR LED. A range of 5mm LEDs offering several different colour options. Comprises of two LEDs connected in inverse parallel, housed in a milky white package. Applications include polarity indication etc.

| | lF | VF | VF | VR | Int.at IF | View | Wave | |
|--------|-------|---------|----------|---------|------------|-------|--------|-------|
| | max. | typ. | max. | max. | mcd. | angle | length | |
| Red | 30mA | 2V | 2.5V | 5V | 40 @ 20mA | 60° | 625 | |
| Green | 30mA | 2.2V | 2.5V | 5V | 40 @ 20mA | 60° | 565 | |
| Yellow | 30mA | 2.1V | 2.5V | 5V | 40 @ 20mA | 60° | 590 | |
| CODE | T | /PE | | | | | | PRICE |
| LED44 | 10 5r | nm Bi-c | colour L | .ED Re | d/Green | | | £0.50 |
| LED45 | 50 5r | nm Bi-c | colour L | .ED Re | d/Yellow | | | £0.50 |
| LED46 | 60 5r | nm Bi-c | colour L | .ED Gre | een/Yellow | | | £0.50 |

5V and 12V LEDS. A range of 5mm LEDs incorporating an inbuilt series resistor enabling the LED to be directly connected to 5 or 12V supply lines. All devices are intensity and colour matched, housed in a coloured diffused package. Sold individually or in packs of 100.

| | | • | | | _ | | |
|------------|--------|------|------|--------|-----------|-------|--------|
| | lF | VF | VF | Ptot | Int at IF | View | Wave |
| | max. | typ. | max. | mW max | mcd. | angle | length |
| 5V HE Red | 17.5mA | 6V | 5V | 310 | 80 @ 10mA | 120° | 630 |
| 5V Green | 17.5mA | 6V | 5V | 310 | 32 @ 10mA | 120° | 565 |
| 5V Yellow | 17.5mA | 6V | 5V | 310 | 32 @ 10mA | 120° | 590 |
| 12V HE Red | 11.5mA | 14V | 5V | 310 | 80 @ 10mA | 120° | 630 |
| 12V Green | 11.5mA | 14V | 5V | 310 | 32 @ 10mA | 120° | 565 |
| 12V Yellow | 11.5mA | 14V | 5V | 310 | 32 @ 10mA | 120° | 590 |
| | | | | | | | |
| CODE | TVDE | | | | | | DDICE |

| CODE | TYPE | PRICE |
|--------|--------------------|-------|
| LED350 | 5mm 5V LED HE Red | £0.35 |
| LED360 | 5mm 5V LED Green | £0.35 |
| LED370 | 5mm 5V LED Yellow | £0.35 |
| LED380 | 5mm 12V LED HE Red | £0.35 |
| LED390 | 5mm 12V LED Green | £0.35 |
| LED400 | 5mm 12V LED Yellow | £0.35 |
| | | |

WHEN PLACING AN ORDER PLEASE USE THE FULL ORDER CODE INCLUDING ANY PUNCTUATION MINIMUM ORDER VALUE £15.00

FLASHING LED's

FLASHING 3mm LED. A range of 3mm LEDs in a diffused coloured package with an inbuilt IC to produce a continuous flash at a frequency of 3Hz. No series resistor required in the supply range 9-12V dc.

| | l _F max. | VF typ. | V _F max. | V _R max. | Int.at IF mcd. | View angle | Wave length |
|--------|------------------------|------------|------------------------|------------------------|-------------------|---------------|----------------|
| HE Red | 38-56mA | 9-12V | 13V | 0.5V | 32 @ 9V | 60° | 625 |
| Green | 38-56mA | 9-12V | 13V | 0.5V | 20 @ 9V | 60° | 565 |
| Yellow | 38-56mA | 9-12V | 13V | 0.5V | 20 @ 9V | 60° | 590 |
| Blue | 20mA | 5-14V | 4.2V | 5V | 60 @ 9V | 60° | 468 |
| | | | | | | | |

| CODE | TYPE | PRICE |
|---------|-----------------------------------|--------------|
| LED591 | Flashing LED 3mm Red Pack of 2 | £1.50 |
| LED601 | Flashing LED 3mm Green Pack of 2 | £1.50 |
| LED611 | Flashing LED 3mm Yellow Pack of 2 | £1.50 |
| 620-064 | Flashing LED 3mm Blue SINGLE | £2.50 |
| | | |

FLASHING LED 5mm. A range of 5mm LEDs in a diffused coloured package with an inbuilt IC to produce a continuous flash at a frequency of 3Hz. No series resistor required in the supply range of 9-12V dc.

| | lF | VF | VF | VR | Int.at I⊧ | View | Wave |
|--------|------|-------|------|------|-----------|-------|--------|
| | max. | typ. | min. | max. | mcd. | angle | length |
| Red | 50mA | 9-12V | 3.5V | 0.5V | 8 @ 9V | 120° | 660 |
| Green | 50mA | 9-12V | 3.5V | 0.5V | 32 @ 9V | 120° | 565 |
| Yellow | 50mA | 9-12V | 3.5V | 0.5V | 32 @ 9V | 120° | 590 |
| Blue | 20mA | 5-14V | 4.2V | 5V | 80 @ 9V | 60° | 468 |

| CODE | TYPE | PRICE |
|---------|-----------------------------------|-------|
| LED620 | Flashing LED 5mm Red Pack of 2 | £1.20 |
| LED630 | Flashing LED 5mm Green Pack of 2 | £1.20 |
| LED640 | Flashing LED 5mm Yellow Pack of 2 | £1.20 |
| 620-065 | Flashing LED 5mm Blue SINGLE | £2.50 |

FLASHING LED 8mm. A range of 8mm LEDs in a diffused coloured package with an inbuilt IC to produce a continuous flash of 3Hz. Within the supply voltage of 9-12V dc no series resistor is required.

| | lF to one | VF | VF | VR | Int.at IF | View | Wave |
|--------|--------------|-------|------|------|-----------|-------|--------|
| | typ. | typ. | min. | max. | mcd. | angle | length |
| Red | 45mA | 9-12V | 3.5V | 0.5V | 100 @ 9V | 140° | 625 |
| Green | 45mA | 9-12V | 3.5V | 0.5V | 70 @ 9V | 140° | 565 |
| Yellow | 45mA | 9-12V | 3.5V | 0.5V | 70 @ 9V | 140° | 595 |
| Blue | 20mA | 5-14V | 4.2V | 5V | 75 @ 9V | 60° | 468 |

| CODE | TYPE | PRICE |
|---------|------------------------------|-------|
| LED650 | Flashing LED 8mm Red Each | £0.95 |
| LED660 | Flashing LED 8mm Green Each | £0.95 |
| LED670 | Flashing LED 8mm Yellow Each | £0.95 |
| 620-066 | Flashing LED 8mm Blue SINGLE | £2.60 |


FLASHING LED 10mm. A range of 10mm LEDs in a diffused coloured package with an inbuilt IC to produce a continuous flash of 3Hz. Within the supply voltage of 9-12V dc no series resistor is required.

| | | | | - | | | |
|--------|------------------------|------------------------|------------------------|------------------------|-------------------|---------------|----------------|
| | l _F max. | V _F typ. | V _F min. | V _R max. | Int.at IF mcd. | View angle | Wave length |
| Red | 56mA | 9-12V | 3.5V | 0.5V | 100 @ 9V | 60° | 625 |
| Green | 56mA | 9-12V | 3.5V | 0.5V | 70 @ 9V | 60° | 565 |
| Yellow | 56mA | 9-12V | 3.5V | 0.5V | 70 @ 9V | 60° | 590 |
| Blue | 20mA | 5-14V | 4 2V | 5V | 70 @ 9V | 60° | 468 |

| TYPE | PRICE |
|-------------------------------|---|
| Flashing LED 10mm Red EACH | £0.95 |
| Flashing LED 10mm Green EACH | £0.95 |
| Flashing LED 10mm Yellow EACH | £0.95 |
| Flashing LED 10mm Blue SINGLE | £2.99 |
| | Flashing LED 10mm Red EACHFlashing LED 10mm Green EACHFlashing LED 10mm Yellow EACH |


LED PANEL CLIPS AND HOLDERS

LED PANEL CLIPS one part 3mm and two part 5mm clips to suit the 3 and 5mm LED's listed.



| CODE | TYPE | PRICE |
|--------|-------------------------------|-------|
| LEC680 | 3mm LED Panel Clip Pack of 10 | £0.75 |
| LEC690 | 5mm LED Panel Clip Pack of 10 | £0.99 |

5mm BEZEL CLIPS attractive push fit panel clips in black nylon, offering a professional appearance at low cost. Prominent or recessed styles. Panel cutout 8mm.




| CODE | TYPE | PRICE |
|--------|------------------------------------|-------|
| LEC702 | 5mm Bezel Clip Prominent Pack of 5 | £1.50 |
| LEC705 | 5mm Bezel Clip Recessed Pack of 5 | £1.50 |

CHROME BEZEL LED HOLDERS attractive chrome plated brass recessed LED bezels which form a high quality panel product. The LED is held in position by a simple retaining mount which push fits into the rear of the holder. Supplied complete with mounting nut and washer. Panel cutout for the 5mm type - 8mm, and 6.3mm for the 3mm type.


| CODE | TYPE | PRICE |
|--------|-----------------------------|-------|
| LEC710 | Chrome Bezel LED Holder 3mm | £0.70 |
| LEC720 | Chrome Bezel LED Holder 5mm | £0.70 |

8mm BEZEL PANEL CLIP attractive push fit panel clip for 8mm LED's in black nylon offering a professional finish at low cost. Panel cutout required 12mm.



| CODE | TYPE | PRICE |
|--------|---------------------------|--------------|
| LEC730 | 8mm Bezel Panel Clip EACH | £0.35 |

10mm BEZEL PANEL CLIP attractive push fit panel clips for 10mm LED's in black nylon offering a professional finish at low cost. Panel cutout required 14mm.




CODE **TYPE** PRICE 10mm Bezel Panel Clip EACH..... LEC740 £0.40

SOLDERLESS LED CONNECTOR

SOLDERLESS LED CONNECTOR a novel LED connector with 200mm leads pre-stripped and tinned, which simply clips to the

rear of the LED and is retained in position by a patented clamping device. Suitable for use with LED's with leads on 2.54mm pitch. Dimensions 14.5 x 2.6mm. Moulded in Toray with UL94V-0.



0.25W CARBON FILM RESISTORS

CARBON FILM 0.25W RESISTORS miniature high stability 0.25W carbon film resistors. 2 common preferred values. Supplied in packs of 10. Full range of values available.

Technical Specification Power Rating@70°C 0.25W 0Ω - 10MΩResistance Range Tolerance ±5% Temp. Coefficient ±400ppm/°C Operating Voltage Max 300V Temperature Range -25°C to +70°C **Dimensions Body** 6.5 x 2.3mm 30 x 0.6mm Leads

| CODE | TYPE | PRICE |
|---------|------------------------------------|-------|
| 680-265 | Carbon Film Resistor 0.25W 470 Ohm | £0.40 |
| 680-305 | Carbon Film Resistor 0.25W 1K Ohm | £0.40 |

GRAIN OF RICE BULBS

1.5 VOLT GRAIN OF RICE BULBS a micro miniature filament lamp that features a bulb measuring just 1.4mm diameter. Suitable for a wide range of industrial and hobbyist applications such as: LCD backlighting, general indication, close-proximity illumination, model railways, dolls houses. Uninsulated leads, low voltage operation. Filament shape C2R 1.5 volts 15mA.

| | G.S. | |
|---------|---|--------------|
| CODE | TYPE | PRICE |
| 41-0186 | Grain of Rice Bub 1.5V Clear Pack of 5 | £0.99 |
| 41-0187 | Grain of Rice Bub 1.5V Clear Pack of 25 | £4.50 |

12 VOLT GRAIN OF RICE BULBS a range of sub-miniature

coloured bulbs with 120mm insulated wire leads. 1.8mm dia x 5mm length. 12 volt 30mA.



| CODE | TYPE | PRICE |
|---------|--|-------|
| 622-936 | G.O.R. Bulb 12V 120mm Lead Clear | £0.80 |
| 622-940 | G.O.R. Bulb 12V 120mm Lead Red | £0.80 |
| 622-952 | G.O.R. Bulb 12V 120mm Lead Green | £0.80 |
| 622-944 | G.O.R. Bulb 12V 120mm Lead Amber | £0.80 |
| 622-948 | G.O.R. Bulb 12V 120mm Lead Yellow | £0.80 |
| 622-956 | G.O.R. Bulb 12V 120mm Lead Blue | £0.80 |
| 622-938 | G.O.R. Bulb 12V 120mm Lead Clear Pack of 5 | £3.60 |
| 622-942 | G.O.R. Bulb 12V 120mm Lead Red Pack of 5 | £3.60 |
| 622-954 | G.O.R. Bulb 12V 120mm Lead Green Pack of 5 | £3.60 |
| 622-946 | G.O.R. Bulb 12V 120mm Lead Amber Pack of 5. | £3.60 |
| 622-950 | G.O.R. Bulb 12V 120mm Lead Yellow Pack of 5. | £3.60 |
| 622-958 | G.O.R. Bulb 12V 120mm Lead Blue Pack of 5 | £3.60 |
| | | |

FREE PARKING FOR 2 HOURS OUTSIDE OF OUR SHOP

GRAIN OF WHEAT BULBS

CLEAR GRAIN OF WHEAT BULB WIRE ENDED a miniature T1 lamp with 35mm wire leads in 5V and 12V. 3.18mm dia x 5.35mm.

| Voltage | Current | Life(hrs |) |
|---------|-----------|-----------|-----------------------------------|
| 5V | 45mA | 10,000 | |
| 12V | 60mA | 16,000 | |
| CODE | TYPE | | PRICE |
| ML0023 | G.O.W. Bu | ılb Clear | Wire Ended 5V Pack of 5 £1.75 |
| MLBP23 | G.O.W. Bu | ılb Clear | Wire Ended 5V Pack of 25 £7.99 |
| ML0025 | G.O.W. Bu | ılb Clear | Wire Ended 12V Pack of 5 £1.75 |
| MLBP25 | G.O.W. Bu | ılb Clear | Wire Ended 12V Pack of 25 £7.99 |
| MLSP25 | G.O.W. Bu | ılb Clear | Wire Ended 12V Pack of 100.£29.99 |
| | | | |

CLEAR GRAIN OF WHEAT BULBS miniature clear bulbs. 3.2mm dia x 10mm length, with 120mm insulated wire leads.

Available in 3 voltages:- 3V 120mA, 6V 65mA, 12V 65mA.



| CODE | TYPE PRICE |
|--------|--|
| ML0005 | Grain of Wheat Bulb Clear 3V Pack of 5 £1.75 |
| MLBP05 | Grain of Wheat Bulb Clear 3V Pack of 25 £7.99 |
| MLSP05 | Grain of Wheat Bulb Clear 3V Pack of 100 £29.99 |
| ML0010 | Grain of Wheat Bulb Clear 6V Pack of 5£1.45 |
| MLBP10 | Grain of Wheat Bulb Clear 6V Pack of 25 £6.50 |
| MLSP10 | Grain of Wheat Bulb Clear 6V Pack of 100 £24.99 |
| ML0020 | Grain of Wheat Bulb Clear 12V Pack of 5£1.45 |
| MLBP20 | Grain of Wheat Bulb Clear 12V Pack of 25 £6.50 |
| MLSP20 | Grain of Wheat Bulb Clear 12V Pack of 100 £24.99 |

COLOURED GRAIN OF WHEAT BULBS

COLOURED GRAIN OF WHEAT BULBS miniature coloured bulbs with 25mm wire leads, 3.2mm diameter x 8.2mm length. 12V 65mA.

| | FLORISE 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 | |
|--------|---|-------|
| CODE | TYPE | PRICE |
| ML0030 | Grain of Wheat Bulb Red 12V Pack of 5 | £1.65 |
| ML0040 | Grain of Wheat Bulb Green 12V Pack of 5 | £1.65 |
| ML0050 | Grain of Wheat Bulb Yellow 12V Pack of 5 | £1.65 |
| ML0060 | Grain of Wheat Bulb Blue 12V Pack of 5 | £1.65 |

3 VOLT COLOURED GRAIN OF WHEAT BULBS a range of miniature coloured bulbs with 120mm insulated wire leads. 3.2mm dia x 7mm length. 3 volt 120mA.

| CODE | TYPE | PRICE |
|---------|---|-------|
| 622-900 | G.O.W. Bulb 3V 120mm Lead Red | £0.50 |
| 622-908 | G.O.W. Bulb 3V 120mm Lead Green | £0.50 |
| 622-904 | G.O.W. Bulb 3V 120mm Lead Amber | £0.50 |
| 622-912 | G.O.W. Bulb 3V 120mm Lead Blue | £0.50 |
| 622-902 | G.O.W. Bulb 3V 120mm Lead Red Pack of 5 | £2.35 |
| 622-910 | G.O.W. Bulb 3V 120mm Lead Green Pack of 5 | £2.35 |
| 622-906 | G.O.W. Bulb 3V 120mm Lead Amber Pack of 5 | £2.35 |
| 622-914 | G.O.W. Bulb 3V 120mm Lead Blue Pack of 5 | £2.35 |
| | | |

WHEN PLACING AN ORDER PLEASE USE THE FULL ORDER CODE INCLUDING ANY PUNCTUATION MINIMUM ORDER VALUE £15.00 6 VOLT COLOURED GRAIN OF WHEAT BULBS a range of

miniature coloured bulbs with 120mm insulated wire leads. 3.2mm dia x7mm length. 6 volt 50mA.



| CODE | TYPE | PRICE |
|---------|--|-------|
| 622-916 | G.O.W. Bulb 6V 120mm Lead Red | £0.50 |
| 622-924 | G.O.W. Bulb 6V 120mm Lead Green | £0.50 |
| 622-920 | G.O.W. Bulb 6V 120mm Lead Amber | £0.50 |
| 622-932 | G.O.W. Bulb 6V 120mm Lead Yellow | £0.50 |
| 622-928 | G.O.W. Bulb 6V 120mm Lead Blue | £0.50 |
| 622-918 | G.O.W. Bulb 6V 120mm Lead Red Pack of 5 | £2.35 |
| 622-926 | G.O.W. Bulb 6V 120mm Lead Green Pack of 5 | £2.35 |
| 622-922 | G.O.W. Bulb 6V 120mm Lead Amber Pack of 5 | £2.35 |
| 622-934 | G.O.W. Bulb 6V 120mm Lead Yellow Pack of 5 | £2.35 |
| 622-930 | G.O.W. Bulb 6V 120mm Lead Blue Pack of 5 | £2.35 |

12 VOLT COLOURED GRAIN OF WHEAT BULBS a range of

miniature coloured bulbs with 120mm insulated wire leads. 3.2mm dia x 10mm length. 12 volt 80mA.




| CODE | TYPE | PRICE |
|--------|---|-------|
| ML0035 | G.O.W. Bulb 12V 120mm Lead Red | £0.40 |
| ML0045 | G.O.W. Bulb 12V 120mm Lead Green | £0.40 |
| ML0055 | G.O.W. Bulb 12V 120mm Lead Yellow | £0.40 |
| ML0065 | G.O.W. Bulb 12V 120mm Lead Blue | £0.40 |
| ML0036 | G.O.W. Bulb 12V 120mm Lead Red Pack of 5 | £1.80 |
| ML0046 | G.O.W. Bulb 12V 120mm Lead Green Pack of 5. | £1.80 |
| ML0056 | G.O.W. Bulb 12V 120mm Lead Yellow Pack of 5 | £1.80 |
| ML0066 | G.O.W. Bulb 12V 120mm Lead Blue Pack of 5 | £1.80 |

LES BULBS AND HOLDERS

LES BULBS miniature tubular filament bulbs, 5mm diameter x

16mm including screw fitting. 6V 60mA 24V 40mA.



| CODE | TYPE | PRICE |
|---------|-------------------------------|-------|
| 18-0026 | LES Bulb Clear 1.5V Pack of 5 | £1.65 |
| 18-0028 | LES Bulb Clear 4.5V Pack of 5 | £1.65 |
| ML0100 | LES Bulb Clear 6V Pack of 5 | £2.25 |
| ML0110 | LES Bulb Clear 12V EACH | £0.45 |
| ML0111 | LES Bulb Clear 12V Pack of 5 | £2.15 |
| ML0112 | LES Bulb Clear 24V EACH | £0.50 |
| | | |

LES HOLDER a miniature LES holder with solder tag connections.

Dimensions:- 15mm across tags. 9mm high, x 6mm dia.



| CODE | TYPE | PRICE |
|--------|--------------------------|-------|
| MLH160 | LES Lampholder | £0.45 |
| MLH161 | LES Lampholder Pack of 5 | £2.15 |

LES LAMPHOLDERS WITH COLOURED LENS attractive LES holders with a flat top polycarbonate lens. Solder tag termination and chrome bezel. Overall length 27mm, panel cutout required 11mm.

| CODE | TYPE | PRICE |
|--------|-----------------------------|-------|
| MLH170 | LES Holder with Red Lens | £0.99 |
| MLH180 | LES Holder with Green Lens | £0.99 |
| MLH190 | LES Holder with Orange Lens | £0.99 |

MES BULBS AND HOLDERS

MES BULBS a range of miniature MES lamps available in a range of voltages. 11mm diameter x 23mm length overall.

1.5V 300mA - nominal life 50 hrs. 2.5V 200mA - nominal life 100 hrs. 3.5V 300mA - nominal life 1000 hrs. 6V 40mA - nominal life 100 hrs. 6V 60mA - nominal life 10000 hrs. 12V 200mA - nominal life 3000 hrs. 24V 50mA - nominal life 50 hrs. 24V 125mA - nominal life 50 hrs.



| 24 V 123111A | - Horrillar life 50 fils. | T |
|--------------|----------------------------|-------|
| CODE | TYPE | PRICE |
| ML0212 | MES Bulb 1.5V 300mA | £0.30 |
| ML0213 | MES Bulb 1.5V 300mA 5 pack | £1.45 |
| ML0214 | MES Bulb 2.5V 200mA | £0.30 |
| ML0215 | MES Bulb 2.5V 200mA 5 Pack | £1.45 |
| ML0216 | MES Bulb 3.5V 300mA | £0.30 |
| ML0217 | MES Bulb 3.5V 300mA 5 Pack | £1.45 |
| 622-736 | MES Bulb 6V 40mA | £0.30 |
| ML0220 | MES Bulb 6V 60mA | £0.25 |
| ML0221 | MES Bulb 6V 60mA 5 Pack | £1.20 |
| ML0230 | MES Bulb 12V 200mA | £0.25 |
| ML0231 | MES Bulb 12V 200mA 5 Pack | £1.20 |
| ML0146 | MES Bulb 24V 125mA | £0.30 |

LENS ENDED MES BULB a lens ended bulb with MES base producing a focused beam of light. Commonly used in torches and applications where a directed beam is required. Max diameter 9.5mm, overall length 24mm.

Technical Specification



MES LAMPHOLDER a miniature MES bulb holder with two solder tag connections.

19mm across tags.

13mm high. 10mm dia.

| CODE | TYPE | PRICE |
|--------|--------------------------|-------|
| MLH250 | MES Lampholder | £0.25 |
| MLH260 | MES Lampholder Pack of 5 | £1.25 |

MES BATTEN HOLDER a MES bulb holder with black plastic

body and crosshead screw terminals Fixing centres 22mm.

29mm diameter x 19m high.

| CODE | TYPE | PRICE |
|--------|-----------------------------|-------|
| MLH270 | MES Batten Holder | £0.50 |
| MLH280 | MES Batten Holder Pack of 5 | £2.25 |

ALARM MIMIC INDICATOR

FLASHING LED ALARM MIMIC a flashing LED in a mounting bezel designed for fitting in the dashboard to indicate an alarm is armed, even if none is installed. Fitted with a 1.5m lead. 12Vdc, 10mA



PANEL INDICATORS

12V INDICATORS a range of 12V indicator lamps with 9mm x 9mm square heads or 14mm diameter round heads. All plastic. Solder connections. **Available while stocks last**.



| CODE | TYPE | PRICE |
|---------|------------------------------------|--------------|
| 622-812 | 12V Square Indicator 9 x 9mm Blue | £1.25 |
| 622-816 | 12V Round Indicator 9mm Dia Red | £1.25 |
| 622-818 | 12V Round Indicator 9mm Dia Blue | £1.25 |
| 622-820 | 12V Round Indicator 9mm Dia Green | £1.25 |
| 623-792 | 12V Round Indicator 14mm Dia Red | £1.45 |
| 623-794 | 12V Round Indicator 14mm Dia Blue | £1.45 |
| 623-793 | 12V Round Indicator 14mm Dia Green | £1.45 |
| | | |

SOLAR PANELS

SOLAR MODULES a range of encapsulated solar cell modules mounted in a black polycarbonate case. The faceplate consists of small bubble magnifiers which maximises performance by enhancing the light as it strikes the cell. All the modules have an output of 0.45V and are fitted with threaded stud terminals. The modules can be connected in series to produce the required voltage. Out-

put current ranges from 100mA to 800mA.

| Code | Dimensions:- |
|--------|-----------------|
| SOM100 | 45 x 26 x 7.5mm |
| SOM200 | 53 x 36 x 7.5mm |
| SOM400 | 74 x 45 x 7.5mm |
| SOM800 | 95 x 65 x 7.5mm |
| | |

| - | BRANKE |
|---------|-------------|
| | |
| | |
| Million | 对以外来 |

| CODE | TYPE | PRICE |
|--------|--------------------|-------|
| SOM100 | Solar Module 100mA | £1.90 |
| SOM200 | Solar Module 200mA | £2.50 |
| SOM400 | Solar Module 400mA | £3.80 |
| SOM800 | Solar Module 800mA | £7.50 |
| | | |

BOTTLE/CLIP ON LAMP FITTINGS

BOTTLE LAMP ADAPTOR a lamp holder which fits into the neck of a bottle with an opening of 17 - 19mm diameter. Maximum bulb size 60 watt BC. Fitted with 1.8M approx of flex with BS plug.



| CODE | TYPE | PRICE |
|---------|--|-------|
| 560-051 | Bottle Lamp Adaptor with Flex and Plug | £4.99 |

CLIP-ON LAMP ADAPTOR a lamp holder fitted with a strong clip suitable fitting the lamp to a shelf etc. Ideal for additional temporary lighting. Can be fitted with a shade. Maximum bulb size 100 watt BC. Fitted with 1.8M approx of flex with BS plug.



| CODE | TYPE | PRICE |
|---------|---------------------------------------|-------|
| 560-053 | Clip-On Lamp Adaptor with Flex & Plug | £4.99 |

FIXED VOLTAGE SWITCH MODE PSU

ENERGY EFFICIENT SWITCH-MODE PSU compact, energy efficient switch-mode power supplies giving up to 500mA 6V type (20-0442) or 1000mA 9V and 12V type 20-0444 and 20-0446. Suitable for most low power electronic products such as MP3 players, PDA etc. Supplied with 8 adaptors.

Power max. 3W/9W/12W Input voltage 100-240Vac, Output current max. 6V 500mA - 9/12v1000mA Output voltage 6Vdc/9Vdc/12vDC



| CODE | TYPE PRICE | |
|---------|---|--|
| 20-0442 | Energy Efficient S/Mode PSU 6Vdc 500mA £8.99 | |
| 20-0444 | Energy Efficient S/Mode PSU 9Vdc 1000mA £11.99 | |
| 20-0446 | Energy Efficient S/Mode PSU 12Vdc 1000mA £11.99 | |

ENERGY EFFICIENT SWITCH-MODE PSUs 12v these energy efficient switch-mode power supplies give up to 3000mA/5000mA at 12Vdc. Suitable for most low power electronic products such as CCTV and LED installation tape installation. Use 25% less power. Power max. 36W /60W. Adaptor plug 5 x 2.1mm

Input voltage 100-240Vac Max current 20-0447 - 3000mA 20-0445 - 5000mA Output voltage 12Vdc Dims 110 x 45 x 30mm



| CODE | TYPE | PRICE |
|---------|------------------------------------|--------|
| 20-0447 | Energy Eff S/Mode PSU 12Vdc 3000mA | £25.99 |
| 20-0448 | Energy Eff S/Mode PSU 12Vdc 5000mA | £39.99 |

SWITCH-MODE 13.8V BENCH TOP POWER SUPPLIES a range of 13.8Vdc power supplies feature electronic voltage control and short-circuit protection. Ideal for powering CB Radios, communication transceivers and other appliances. Sturdy case fitted with a mains lead and plug. Output via a red and a black terminals. Available 3 amp or 5amp ooutputs.

Specification

Power supply 220-240Vac 50Hz Output voltage 13.8Vdc Dimensions 130 x 92 x 65mm Weight 470g



| CODE | TYPE | PRICE |
|---------|--|--------|
| 20-0655 | Bench Top Switch Mode PSU 13.8Vdc 3A/41W | £22.99 |
| 20-0656 | Bench Top Switch Mode PSU 13.8Vdc 5A/69W | £25.99 |

WHEN PLACING AN ORDER PLEASE
USE THE FULL ORDER CODE
INCLUDING ANY PUNCTUATION

MINIMUM ORDER VALUE £15.00

ADJUSTABLE VOLTAGE SWITCH MODE PSU

ENERGY EFFICIENT SWITCH-MODE PSU a range of compact, energy efficient switch-mode power supplies gives up to 1000mA from 3V to 12V. Uses 25% less power and suitable for most low power electronic products such as MP3 players, PDA etc. Up to 1500mA at all output voltages. Supplied with 8 adaptor plugs.

Specification

Power max. 7.5W/12W /18W Input voltage 100-240Vac, Output current max. 600mA/1000mA/1500mA (all output voltages) Output voltage 3.0/4.5/5.0/6.0/7.5/9.0/12.0 Vdc



| CODE | TYPE PRICE |
|---------|--|
| 20-0400 | Energy Eff Switch Mode PSU 600mA 3 - 12Vdc £12.99 |
| 20-0401 | Energy Eff Switch Mode PSU 1000mA 3 - 12Vdc £12.99 |
| 20-0403 | Energy Eff Switch Mode PSU 1500mA 3 - 12Vdc £14.99 |

SWITCH MODE POWER SUPPLIES a range of stabilised switch mode power supplies which are short circuit and overload protected. Each is supplied with 7 plugs including walkman, Sony and Aiwa personal stereo plugs. 2 types are available:-

Model 640-404 is a plug-in type with 6 switchable outputs of:- 9, 12 & 15Vdc @ 1500mA, max 22.5VA, 18 & 20 Vdc @ 1200mA, max 24VA and 24Vdc @ 1000mA, max 24VA. It is supplied with 7 plugs which can be reversed to change the polarity of the plug. Power lead length 1.8m.

Model 640-405 is supplied with a mains lead which is fitted with a 13A BS plug and an IEC socket which connect to the power supply. The output is via 2 terminal posts which will accept 4mm banana plugs, spades or bare wires. An output lead is also supplied which is fitted with spade connectors one end and a socket at the other which will accept the interchangeable plugs. The plugs are reversible so the polarity can be reversed. The 640-405 has output voltages of:-

3, 5, 6, 9 & 12Vdc @2.5A max 30VA, 13.8Vdc @2.2A max30VA.



SWITCH-MODE DESKTOP POWER SUPPLY 2500mA a lightweight, low profile in-line power supply which uses the latest

switch mode technology. It has a regulated 12 volt output and short circuit, overload and thermal protection. With a power indicator and figure 8 mains lead. Very reliable and efficient it is ideal for CCTV cameras.

Specification:

Power supply 100-240Vac, 50/60Hz (30W)

Output voltage 12Vdc
Max. current 2500mA
Dimensions 95 x 45 x 28mm

Weight 193g



CODE TYPE PRICE
640-684 Switch-Mode Power Supply 12Vdc/2500mA....... £19.99

UNIVERSAL SWITCH-MODE POWER SUPPLY 4000mA a compact, lightweight 70W switch-mode PSU includes 8 interchangeable tips, which support most laptops and portable devices such as PDA and MP3 players. Ideal as a replacement, upgrade or spare power supply. Features Power ON indicator, Voltage selectionvia slide switch. Overload and short circuit protected

Power max. 70W Input voltage 110 - 240Vac Max. current 4000mA Output voltage 12/15/16/18/19/ 20/24Vdc Dims 115 x 58 x 37mm



CODE **TYPE** Universal Switch Mode PSU 4000mA 12-24Vdc.. £29.99 20-1120

UNIVERSAL SWITCH-MODE POWER SUPPLY 5000mA a 90W switch mode PSU which includes 8 interchangeable tips, which support most laptops and portable devices such as PDA and MP3 players. It can be powered via mains supply or in-car. Ideal as a replacement, upgrade or spare power supply. Features Power ON indicator, Voltage selection via slide switch. Overload and short circuit protected. Adjustable output voltages: 12 - 24Vdc; 5V @ 500mA USB charger.

Input voltage 110 - 240Vac / 11 - 14Vdc Max. current 5000mA Output voltage 12/15/16/18/ 19/20/24Vdc

20-1126



Universal Switch Mode PSU 5000mA 12-24Vdc.. £46.99

UNIVERSAL SWITCH-MODE POWER SUPPLY 6000mA a120W switch-mode PSU includes 8 interchangeable tips, which support most laptops and portable devices such as PDA and MP3 players. Ideal as a replacement, upgrade or spare power supply. Features Power ON indicator, Voltage selection via slide switch. Overload and short circuit protected. Adjustable output voltages: 15 -24Vdc; 5V @ 500mA USB charger.

Input voltage 110-240Vac Max. current 6000mA Output voltage 15/16/18/19 /20/22/24Vdc Dims 155 x 65 x 38mm



CODE **TYPF PRICE** 20-0123 Universal Switch Mode PSU 6000mA 15-24Vdc.. £37.99

SWITCH-MODE DESK TOP POWER SUPPLY 7500mA a light-

weight, switch mode PSU. It has a regulated voltage output selectable in 1V steps with voltage rated inserts and features short circuit, overload and thermal protection. It is supplied with mains lead and 8 DC power plugs.

Specification:

Power supply 100-240Vac, 50/60Hz(70W) Output voltage 5 - 24Vdc

7500mA @ 5V, Max. current

5000mA @ 12V, 2700mA @ 24V

Dimensions 37 x 57.5 x 142mm



PRICE CODE 640-081 Switch-Mode Power Supply 5 - 24Vdc/7500mA... £40.99

REGULATED BENCH POWER SUPPLIES

REGULATED 13.8V POWER SUPPLIES a range of regulated 13.8Vdc power supply featuring an electronic control and a protection circuit. Short circuit resistant 'Fold Back' current protection. Sturdy case fitted with an earthed mains plug. Power 230V/50Hz (fuse protected). ON/OFF switch with indicator. Output via red and black 4mm terminals. Designed for use in well ventilated areas. Note:- Continuous current is the maximum continuous current that may be drawn, the Maximum current is the maximum for a 50% duty cycle, the Peak current is the maximum surge. See table below.

Specifications



| 650-667 | 15A | 25A | 27A | 165 x 170 x 195 | imm |
|---------|------------|------------|------------|-----------------|--------|
| CODE | TYPE | | | | PRICE |
| 650-651 | Reg 13.8Vd | c P/Supply | 2A Continu | ous 3 - 5A | £29.99 |
| 650-652 | Reg 13.8Vd | c P/Supply | 3A Continu | ous 5 - 7A | £40.99 |
| 650-654 | Reg 13.8Vd | c P/Supply | 5A Continu | ous 7 - 9A | £54.99 |
| 650-657 | Reg 13.8Vd | c P/Supply | 7A Continu | ous 10 - 12A | £67.99 |
| 650-667 | Reg 13.8Vd | c P/Supply | 15A Contin | uos 25 - 27A.£ | 119.99 |
| | | | | | |

REGULATED POWER SUPPLY WITH VARIABLE OUTPUT a 0-20V/2A MAX regulated power supply with variable output voltage. Output is via red (+), and black (-) 4mm terminal sockets. Fitted with 2 panel-meters for analogue display of voltage and current and an illuminated mains switch. It is housed in a solid case with a fixed mains lead.

Specification:

Power Supply 230Vac, 50Hz 0 - 20Vdc Output voltage Output current 2A max 110 x 240 x 150mm **Dimensions** Weight

2.8kg

CODE PRICE 640-673 Regulated Power Supply 0-20Vdc/2A Max...... £44.99

BENCHTOP POWER SUPPLY a compact high quality regulated DC power supply which is suitable for the service field, laboratories and hobbyist alike. It offers variable voltage and current outputs which are clearly displayed on LCD meters, it also features 2 independent fixed voltage outputs of 5V and 12V. All outputs are overload and short circuit protected. The power supply is housed in an attractive steel enclosure, and fitted with a BS plug.

Specification

Output voltage 0-30Vdc cont variable Output current 2.5A max cont variable Fixed voltages 5V @ 500mA cont

(1A surge) 12V @ 500mA cont (1A surge)

Line regulation 0.05% ±10mV Load regulation 0.05% ±10mV Dims 150x145x220mm 230V ac 50Hz Power

Weight

CODE **TYPF** PRICE RPS30V Benchtop P/Supply Digital 0-30Vdc/0-2.5A....... £99.99



GAUGEMASTER TRANSFORMERS

GAUGEMASTER CHASSIS MOUNTING TRANSFORMERS a

range of T series chassis mounting mains voltage transformers as

supplied in Gaugemaster controllers. Each unit must be protected by a suitable fuse or circuit breaker. Not suitable for children unless supervised by an adult.



| CODE | TYPE | PRICE |
|------|--|----------|
| T1 | G/Master T/former 25VA 2 x 16V ac 1.25A each | £19.99 |
| T2 | G/Master T/former 25VA 1 x 16V ac 2.5A | . £19.99 |
| T3 | G/Master T/former 25VA 1 x 24V ac 1.25A | . £19.99 |
| T4 | G/Master T/former 25VA 2 x 12V ac 1.25A each | . £19.99 |

GAUGEMASTER UN-REGULATED AC POWER SUPPLIES a

range of un-regulated ac power supplies housed in a metal case. Complete with mains flex and BS 3a fused plug. Output is via choc-bloc connectors and is electrically protected by miniature cir-

cuit breakers. Not suitable for children unless supervised by an adult.



| CODE | TYPE | PRICE |
|------|------------------------------|--------|
| M1 | Power Supply 25VA 2 x 16V AC | £44.99 |
| M2 | Power Supply 25VA 1 x 18V AC | £49.99 |
| M3 | Power Supply 25VA 1 x 24V AC | £49.99 |
| M4 | Power Supply 25VA 2 x 12V AC | £49.99 |

GAUGEMASTER ELECTRONIC TRACK ACCESSORIES

GAUGEMASTER TRACK CLEANER an automatic high frequency electronic track cleaner, model HF1, for permanent connection into your train controller circuit. When poor connection is detected between train and rails a high frequency signal is superimposed on the normal control voltage thereby ionising the air gap and burning off the dirt and residues. The HF1 will work on all types of track gauges from Z to OO, but is not suitable for use with HF lighting generators, multiple train control systems or with accessories that are powered directly from the

Technical Specification

track.

Inputs 10 to 20V AC
@ 20VA max.
Controller Output
0 to 12VDC
Output Connected to Track

FREE PARKING FOR 2 HOURS
OUTSIDE OF OUR SHOP

GAUGEMASTER SUPER SHUTTLE a time controlled unit which can be used with any controller and stops a locomotive at a point

on a line, reverses it and then stops it again at a second point, reversing the locomotive again. This repeats indefinitely. The duration of each sequence can be adjusted from approx 20-70 seconds. Input 16v A.C. at a maximum of 1.25 amps. (Gaugemaster T1 or M1 recommended). Dims: 109mm x 68mm x 20mm



GAUGEMASTER STATION STOP a unit providing an automatic stop and start facility which only requires one reed switch to be installed. The locomotive decelerates for about 5 seconds after

passing the reed switch and stops for approximately 20 seconds as factory set. The time stopped can be adjusted from approx 20-70 seconds, the rate of deceleration is also adjustable. Reed switch and magnet are included. Input 16v A.C. at a maximum of 1.25 amps (Gaugemaster T1 or M1 recommended). Dims: 109mm x 68mm x 20mm



CODE TYPE PRICE
SS2 Gaugemaster Station Stop SS2.....£34.99

GAUGEMASTER CAPACITOR DISCHARGE UNIT a capacitor discharge unit to enable effective operation of point motors from modest power supplies. The unit slowly charges up and stores power up to the maximum voltage of the supply and then when a point motor is connected releases the stored energy. The CDU can operate up to six point motors simultaneously.

Technical Specification

Input 16 to 25V AC max.

Output Connect using Momentary

Action Switches

(not supplied) Dims 70 x 38 x 15mm



SEEP POINT MOTORS

SEEP POINT MOTOR a range of point motors for changing model railway points remotely or automatically, the motor is fixed below the point and the actuator extends up to operate the point. The motor is supplied with the actuator length of 45mm allowing it to be trimmed to suit individual fixing

arrangements. Use with a CDU.

echnical Specification
Input 16 to 25V AC/DC max.
Use of a CCD is recommended.
Dimensions 55 x 16 x 17mm.
Actuator Length 45mm.



| CODE | TYPE | PRICE |
|------|---------------------------------|-------|
| PM1 | Seep Point Motor With Switch | £4.75 |
| PM2 | Seep Point Motor Without Switch | £4.50 |
| PM4 | Seep Point Motor Latching | £5.50 |

PECO LECTRICS

| PECO RAIL JOINERS for the more popular track used. | | | |
|---|---|-------|--|
| CODE | TYPE | PRICE | |
| SL310 | Rail Joiners Nickel Silver N Code 55 Rail | £1.99 | |
| SL311 | Rail Joiners Insulated N Code 55 Rail | £1.69 | |
| SL110 | Rail Joiners Nickel Silver OO/HO Code 75 Rail | £2.20 | |
| SL111 | Rail Joiners Insulated OO/HO Code 75 Rail | £2.20 | |
| SL10 | Rail Joiners Nickel Silver OO/HO Code 100 Rail. | £2.20 | |
| SL11 | Rail Joiners Insulated OO/HO Code 100 Rail | £2.20 | |

PECO PL11 SURFACE MOUNTED POINT MOTOR a side mount-

ed point motor that clips into the side of a setrack or streamline OO/HO code 100 point. This type of motor avoids the need for cutting holes in the base board.



| CODE | TYPE | PRICE |
|------|-------------------------------------|--------------|
| PL11 | Peco Surface Mount Point Motor PL11 | £8.50 |

PECO POINT MOTOR a point motor for changing model railway points remotely or automatically, the motor is fixed below the point

and the actuator extends up to operate the point. Available with a short actuator pin for thin base boards or extended pin of 30mm for fixing under thicker base boards, allowing it to be trimmed to suit individual fixing arrangements.



| CODE | TYPE | PRICE |
|--------|---|-------|
| PL10E | Peco Point Motor Extended Pin | £5.65 |
| PL10 | Peco Point Motor Standard Pin | £5.65 |
| PL10W | Peco Point Motor Low Current | £6.75 |
| PL10WE | Peco Point Motor Low Current Extended Pin | £6.75 |
| | | |

PECO PL9 POINT MOTOR MOUNTING PLATES mounting plate for Peco PL10 point motors. pack of 5.

| CODE | TYPE | PRICE |
|------|---|--------------|
| PL9 | 5 Mounting Plates for Peco Point Motors | £2.69 |

PECO PL12 MOTOR ADAPTOR adaptor base used when fitting Peco point motors above the baseboard.

| CODE | TYPE | PRICE |
|------|--|--------------|
| PL12 | Motor Adaptor Fitted with Over Centre Spring | £1.99 |

PECO PL13 ACCESORY SWITCH a switch that is easily fitted

underneath the Peco point motor to provide electrical switching for frog polarity, signals etc.



CODE TYPE PRICE
PL13 Accessory Switch for Fitting to Peco Point Motor. £3.00

PECO PL15 TWIN MICRO SWITCH fitted to Peco motor PL-10.

The unit has two microswitches to control the polarity of live frogs and signals or to control panel indicators.



| CODE | TYPE | PRICE |
|------|---|-------|
| PL15 | Twin Micro Switch for Fitting to Peco P/Motor | £7.30 |

PECO PL35 CAPACITOR DISCHARGE UNIT a handy safety device, protecting the solenoid turnout motors and passing contact switches: prevents any potential burn-outs. An added bonus is that it will give a welcome boost to your turnout motor, ensuring reliable, positive operation. In most situations only one CDU is

needed for your layout, the transformer is connected to the 'Power in' socket, and the 'Power out' socket is linked to the switch control.



8 5

PECO PL20 TRACK ISOLATION SWITCH clipped onto Peco streamline OO/HO track to bridge isolating gaps. Easy action. In plastic case.

| CODE | TYPE | PRICE |
|------|----------------------------------|--------------|
| PL20 | Peco Track Isolation Switch PL20 | £2.45 |

PECO PL31 CONNECTORS AND SHROUDS a pack of crimp

(Solderless) connectors suitable for use with Peco Electrics terminals. Pack contains 10 connectors and 5 shrouds.



| CODE | TYPE | PRICE |
|------|--|--------------|
| PL31 | Push-on Term'ls & Shrouds for PL22/23/26 5pk | £2.45 |

PECO PL34 WIRING HARNESS a wiring harness for use with

Peco point motors. Comes with a push on connetor and tinned wire ends. Pack contains 2 looms.



| CODE | IYPE | PRICE |
|------|--------------------------|-------|
| PL34 | Peco Wiring Harness PL34 | £4.20 |

PASSING CONTACT SWITCHES a range of passing contact switches use with point motors. The switch makes a contact as it is thrown, the lever then continues to travel to the stop. This indi-

cates the route set without the coil being powered continuously. Suitable for use with makes of point motor. Supplied in a range of 4 colours. The lever will also accept our coloured toggle covers - listed in the switch section of this catalogue.



| CODE | ITPE | PRICE |
|-------|-------------------------------|-------|
| PL26B | Passing Contact Switch Black | £5.69 |
| PL26R | Passing Contact Switch Red | £5.69 |
| PL26W | Passing Contact Switch White | £5.69 |
| PL26Y | Passing Contact Switch Yellow | £5.69 |

PECO LEVER OPERATED SWITCHES a range of switches that match the PL26 series of switches. The range includes an On/Off (SPST) switch and a changeover On/On (SPDT) switch. Can be

used inconjunction with PL27 Switch Console and PL28 Mounting Plates. The lever will also accept our coloured toggle covers - listed in the switch section of this catalogue.



| CODE | TYPE | PRICE |
|------|-------------------------------------|-------|
| PL22 | Peco PL22 L/Op Switch On/Off (SPST) | £5.40 |
| PL23 | Peco PL23 L/Op Switch On/On (SPDT) | £5.40 |

PECO PL27 SWITCH CONSOLE UNIT a switch console unit for use with Peco passing contact switches, on/off and change over

switches (PL26, PL22 & PL23). It will hold 6 switches. Smart appearance, can be mounted to base board It has been designed to fit inside Ratio Signal Box kit No. 536.



PECO PL28 MOUNTING PLATES for use with Peco lever switches Pl22/23/26. Allowing the switches to be mounted onto a control panel.

CODE TYPE PRICE
PL28 Switch Mounting Plate Pack of 6 for PL22/23/26. £2.35

PECO PL24 SWITCH JOINING BARS allows switches to be joined together for multiple switching. and operated simultaneously. Supplied in a pack of 6 bars, each bar is suitable forup to 4 switches. Can be cut as required.

| CODE | TYPE | PRICE |
|------|---|-------|
| PL24 | Switch Joining Bars for use with PL22/23/26 | £2.50 |

PECO PL50 TURNOUT SWITCH MODULE a modular switch unit

for simplified wiring of Peco point motors. There is space for 3 Peco Passing Contact Switches, can be expanded by removing the end cap and using Peco Add-On Module PL51.



| CODE | TYPE | PRICE |
|------|---------------------------------|--------|
| PL50 | Peco Turnout Switch Module PL50 | £16.49 |

PECO PL51 ADD-ON SWITCH MODULE a modular add-on


switch unit to expand the Peco Turnout Switch Module. Simply plugs into the unit.



| CODE | TYPE | PRICE |
|------|--------------------------------|-------|
| PL51 | Peco Switch Module Add-On PL51 | £5.79 |

PROBE FOR USE WITH PL18 STUDS a very simple and effective method of switching turnout motors. Used with studs that are inserted into a track plan panel (2 studs are required for each turnout), the studs are connected to the turnout, the probe is con-

nected to the 16V ac supply, the motor is then operated when the probe contacts the stud.



FREE PARKING FOR 2 HOURS OUTSIDE OF OUR SHOP

PECO LOCO SERVICE CRADLE

PECO PL70 LOCO SERVICE CRADLE a useful aid for loco's and rolling stock to be placed in whilst being serviced. Suitable for OO/HO, N, HOm and OO9. Made in soft foam plastic that will not harm livery or details whilst servicing. Length 255mm.



| CODE | TYPE | PRICE |
|------|---------------------------------|-------|
| PL70 | Peco PL70 Loco Servicing Cradle | £5.99 |

PECO RE-RAILERS

RE-RAILERS a plastic guide for accurate railing of locomotives and rolling stock. Available for N and HO/OO gauges.



TRACKSETTA GAUGES

TRACKSETTA GAUGES a range of metal track setting templates for accurate laying of flexible track. Available for straight and various radi, each is clearly marked for its use. Finished for corrosion protection. Available for N/009 and OO/HO gauges.

| | TRACESSETTA S INCH | |
|---------|--|-------|
| | PATRO INTELES TRACELITA # NCH. | |
| CODE | TYPE | PRICE |
| 640-009 | Tracksetta T/plate N/009 - 228mm/9" Radius | £5.35 |
| 640-011 | Tracksetta T/plate N/009 - 254mm/10" Straight | £5.35 |
| 640-012 | Tracksetta T/plate N/009 - 305mm/12" Radius | £5.35 |
| 640-015 | Tracksetta T/plate N/009 - 381mm/15" Radius | £5.35 |
| 640-018 | Tracksetta T/plate N/009 - 457mm/18" Radius | £5.35 |
| 640-025 | Tracksetta T/plate N/009 - 533mm/21" Radius | £5.35 |
| 640-024 | Tracksetta T/plate N/009 - 610mm/24" Radius | £5.35 |
| 640-035 | Tracksetta T/plate N/009 - 762mm/30" Radius | £5.35 |
| 640-036 | Tracksetta T/plate N/009 - 915mm/36" Radius | £5.35 |
| 640-111 | Tracksetta T/plate OO/HO - 254mm/10" Straight. | £5.35 |
| 640-118 | Tracksetta T/plate OO/HO - 457mm/18" Radius | £5.35 |
| 640-121 | Tracksetta T/plate OO/HO - 533mm/21" Radius | £5.35 |
| 640-125 | Tracksetta T/plate OO/HO - 610mm/24" Radius | £5.35 |
| 640-130 | Tracksetta T/plate OO/HO - 762mm/30" Radius | £5.35 |
| 640-136 | Tracksetta T/plate OO/HO - 915mm/36" Radius | £5.35 |
| 640-142 | Tracksetta T/plate OO/HO - 1067mm/42" Radius | £5.35 |
| 640-148 | Tracksetta T/plate OO/HO - 1219mm/48" Radius | £5.35 |
| 640-160 | Tracksetta T/plate OO/HO - 1524mm/60" Radius | £5.35 |
| | | |

PECO RAIL JOINERS


PECO RAIL JOINERS for the more popular track used.

| CODE | TYPE | PRICE |
|-------|---|-------|
| SL310 | Rail Joiners Nickel Silver N Code 55 Rail | £1.99 |
| SL311 | Rail Joiners Insulated N Code 55 Rail | £1.69 |
| SL110 | Rail Joiners Nickel Silver OO/HO Code 75 Rail | £2.20 |
| SL111 | Rail Joiners Insulated OO/HO Code 75 Rail | £2.20 |
| SL10 | Rail Joiners Nickel Silver OO/HO Code 100 Rail. | £2.20 |
| SL11 | Rail Joiners Insulated OO/HO Code 100 Rail | £2.20 |

24MM COMMERCIAL POTENTIOMETERS

24MM COMMERCIAL POTENTIOMETERS a range of competitive 24mm diameter carbon track single potentiometers suitable for

Chassis mounting with connections made via solder tags, available in popular values. Supplied with standard 6mm nylon shaft.



DIODES

SILICON RECTIFIER DIODES a range of silicon diodes in a plastic case, 1A Rating 1N4000 Series. Sold Individually.

| Technical Specification | | | | | |
|-------------------------|-----------|--------------|--------------|-----------|-------|
| | | V_{RRM} | | V_{RRM} | |
| | 1N4001 | 50V | 1N4004 | 400V | |
| | 1N4002 | 100V | 1N4006 | 800V | |
| | 1N4003 | 200V | 1N4005 | 600V | |
| | | | 1N4007 | 1000V | |
| CODE | TYPE | | | | PRICE |
| 700-000 | Diode Sil | icon Rectifi | er 1N4001 | | £0.06 |
| 700-005 | Diode Sil | icon Rectifi | er 1N4001 8P | k | £0.45 |
| 700-010 | Diode Sil | icon Rectifi | er 1N4002 | | £0.07 |
| 700-015 | Diode Sil | icon Rectifi | er 1N4002 8P | k | £0.50 |
| 700-020 | Diode Sil | icon Rectifi | er 1N4003 | | £0.07 |
| 700-030 | Diode Sil | icon Rectifi | er 1N4004 | | £0.07 |
| 701-360 | Diode Sil | icon Rectifi | er 1N4005 | | £0.07 |
| 700-040 | Diode Sil | icon Rectifi | er 1N4006 | | £0.07 |
| 700-050 | Diode Sil | icon Rectifi | er 1N4007 | | £0.07 |
| | | | | | |


SILICON RECTIFIER DIODES a range of silicon diodes in a plastic case, 3A Rating 1N5400 Series. Sold Individually.

| | _ | - | RA . | - | |
|-------------|---------------|------------|-------------|-----------|-------|
| Technical S | Specification | n | | | |
| | | V_{RRM} | | V_{RRM} | |
| | 1N5401 | 100V | 1N5406 | 600V | |
| | 1N5402 | 200V | 1N5408 | 1000V | |
| | 1N5404 | 400V | | | |
| CODE | TYPE | | | | PRICE |
| 700-100 | Diode Sil | icon Recti | fier 1N5401 | | £0.12 |
| 700-110 | Diode Sil | icon Recti | fier 1N5402 | | £0.12 |
| 700-120 | Diode Sil | icon Recti | fier 1N5404 | | £0.12 |
| 700-130 | Diode Sil | icon Recti | fier 1N5406 | | £0.12 |
| 700-140 | Diode Sil | icon Recti | fier 1N5408 | | £0.12 |
| | | | | | |

1.5A BRIDGE RECTIFIERS miniature 1.5A plastic encapsulated WOO Series rectifiers for direct mounting to PCB's.

Dimensions 5mm High 8mm Dia.








| CODE | TYPE | PRICE |
|---------|--------------------------------|-------|
| 700-920 | Bridge Rectifier 1.5A WOO5 50V | £0.25 |
| 700-925 | Bridge Rectifier 1.5A WO2 200V | £0.25 |
| 700-930 | Bridge Rectifier 1.5A WO4 400V | £0.30 |
| 700-935 | Bridge Rectifier 1.5A WO6 600V | £0.30 |
| 700-940 | Bridge Rectifier 1.5A WO8 800V | £0.35 |

BRIDGE RECTIFIERS miniature 3A plastic encapsulated bridge rectifiers for direct mounting to PCB's.

Dimensions 6.8mm High 15.5mm Square






| CODE | TYPE | PRICE |
|---------|----------------------------------|--------------|
| 700-970 | Bridge Rectifier 3A KBPC102 200V | £0.70 |
| 700-975 | Bridge Rectifier 3A KBPC104 400V | £0.80 |

BRIDGE RECTIFIERS miniature 6A plastic encapsulated bridge rectifiers for direct mounting to PCB's.

Dimensions 6.8mm High 15.5mm Square



| CODE | TYPE | PRICE |
|---------|----------------------------------|-------|
| 700-980 | Bridge Rectifier 6A KBPC602 200V | £1.25 |
| 700-985 | Bridge Rectifier 6A KBPC608 800V | £1.25 |

SPEAKERS & BUZZERS

ULTRA SLIM SUBMINIATURE LOUDSPEAKER a subminiature speaker, 40mm in diameter with an overall depth of just 9.5mm. Paper cone and alnico magnet. Solder tag connection.

Technical Specification

Dimensions 40mm(w) x 9.5mm (d)

 $\begin{array}{ll} \text{Impedance} & 8\Omega \\ \text{Max. power (rms)} & 0.25W \\ \text{Frequency range} & 450\text{Hz} - 5\text{kHz} \\ \text{Magnet weight} & 1.5g \end{array}$



| CODE | TYPE | PRICE |
|---------|---------------------------------------|-------|
| 800-265 | Ultra Slim Submin Loudspeaker 40mm 8Ω | £1.99 |

MINIATURE LOUDSPEAKER a miniature speaker for use in small portable equipment. Fitted with paper cone and ferrite magnets. Solder tag connection. Both types 66mm diameter, 21mm deep.

Handling capacity 300mW.



| CODE | TYPE | PRICE |
|---------|--|-------|
| 800-269 | Miniature Loudspeaker 66mm 8Ω | £1.79 |
| 800-270 | Miniature Loudspeaker 66mm 64 Ω | £1.79 |

WEATHERPROOF LOUDSPEAKER a mylar cored loudspeaker with ferrite magnet for use in exterior environments or where moisture is a problem as the mylar core is unaffected by water. Ideal for use as sounders or warning devices where a wide frequency response is required, door entry systems etc. Nominal 8 ohms

impedance, max power (rms) 0.6W, frequency range 350-4.5KHz. 66mm diameter x 20mm depth.

| CODE | TYPE | PRICE |
|--------|--------------------------|-------|
| SPK150 | Weatherproof Loudspeaker | £2.45 |

MAGNETIC AND CRYSTAL EARPHONES a range of traditional

earphones fitted with 1.8m of twin cable and terminated with a 3.5mm jack plug. Available in either magnetic (low impedance 8Ω) or crystal(high impedance $3M\Omega$).




| CODE | TYPE | PRICE |
|---------|----------------------|-------|
| 800-130 | Earphone Magnetic 8Ω | £0.79 |
| 800-135 | Earphone Crystal 3MΩ | £1.89 |

BUZZERS miniature transistor oscillator buzzers with flying leads or without leads for PCB mounting, offering long life, maximum efficiency with minimum current dissipation.

| <u>l echnical</u> | Specification |
|-------------------|---------------|
| 3V type | 2-5V dc |
| 6V type | 4-9V dc |
| 12V/type | 9-20\/ dc |

Current 25mA 400h7 Frequency Sound output 75dB @ 30cm



| CODE | TYPE | PRICE |
|---------|-----------------------------------|-------|
| 800-100 | Transistor Buzzer 3V With Leads | £1.99 |
| 800-105 | Transistor Buzzer 6V With Leads | £1.99 |
| 800-110 | Transistor Buzzer 12V With Leads | £1.99 |
| 800-115 | Transistor Buzzer 6V PCB Mounting | £1.99 |

MINIATURE PIEZO BUZZER a mini piezo buzzer with flying leads. A rich high output sound with low power consumption.

Technical Specification Sound output 90dB @ 50cm


Current @ 12V 10mA Frequency



| CODE | TYPE | PRICE |
|--------|-----------------------|-------|
| BZP115 | Piezo Buzzer 3-30V dc | £1.90 |

SUB-MINIATURE TOGGLE SWITCHES

SUB-MINIATURE TOGGLE SWITCHES a range of high quality sub-miniature toggle switches in single pole and double pole options. This range of switches is ideal for use when space is at a premium.



Contact rating Initial contact resistance Insulation resistance Contact material

<20mΩ >100MQ at 500V DC

3A, 125V, 1A 250V AC


Copper alloy with silver inlay silver plated **Body Material** Flame retardant alkyd Electrical life >2x104 cycles at full load

| | Operating temperature | -20 C 10 +60 C | | |
|--------|-----------------------|----------------|----------|--------------|
| CODE | TYPE | | ACTION | PRICE |
| SMT010 | Sub-mini Toggle S | PST | .On-Off | £0.80 |
| SMT020 | Sub-mini Toggle S | PDT | On-On | £0.85 |
| | | | CONTINUE | D OVER |

| SMT025 | Sub-mini Toggle SPDT C/OffOn-Off-On | £1.75 |
|---------|---|-------|
| 821-093 | Sub-mini Tog SPDT Biased C/Off.(On)-Off-(On) | £1.75 |
| SMT030 | Sub-mini Toggle DPDTOn-On | £1.40 |
| 821-095 | Sub-mini Toggle DPDT C/OffOn-Off-On | £1.85 |
| 821-094 | Sub-mini Tog DPDT Biased C/Off.(On)-Off-(On). | £1.99 |

MINIATURE TOGGLE SWITCHES

MINIATURE TOGGLE SWITCHES a wide range of high quality miniature toggle switches in single pole and double pole options and with momentary biased action. For biased switching action (On) indicates momentary action.



Contact rating Initial contact resistance Insulation resistance Contact material Body material

Electrical life

6A, 125V, 3A 250V AC <20m**Ω** >100M Ω at 500V DC Copper alloy with silver inlay silver plated

Flame retardant alkyd >5x104 cycles at full load


| | Operating temperature -20°C to +65°C | | |
|-----------|--------------------------------------|----------------|--------------|
| CODE | TYPE | ACTION | PRICE |
| MT0040 | Mini Toggle SPST | .On-Off | £0.75 |
| MT0050 | Mini Toggle SPDT | .On-On | £0.80 |
| MT0060 | Mini Toggle SPDT C/Off | .On-Off-On | £0.85 |
| MTB062 | M/Toggle SPDT Biased One Side | .On-Off-(On) | £1.35 |
| MT0070 | Mini Toggle DPDT | | |
| 820-071 | Mini Toggle DPDT | .On-(On) | £1.90 |
| MT0080 | Mini Toggle DPDT C/Off | On-Off-On | £1.25 |
| MTB082 | M/Toggle DPDT Biased One Side | On-Off-(On) | £1.99 |
| MTB090 | Mini Toggle SPDT Biased C/Off | | |
| MTB100 | Mini Toggle DPDT Biased C/Off | (On)-Off-(On). | £1.75 |
| *** The E | Biased Off switches MTB090 ar | nd MTB100 are | ideal |
| | | | |

for operating solenoids including point motors etc. ***

3 POLE AND 4 POLE MINIATURE TOGGLE SWITCHES a range of high quality miniature toggle switches in 3 pole and 4 pole with

centre off options also being available. Rated 6A @ 125Vac. 3A @ 250Vac.

| Type | Dims (mm) |
|------|-----------|
| 3PDT | 13x18x11 |
| 4PDT | 13x23x11 |



COLOURED TOGGLE LEVER COVERS push fit covers for colour coding mini togale switch levers


| _ | (Switch not include | |
|------|---------------------|--|
| CODE | TVDE | |

| CODE | TYPE | PRICE |
|--------|--------------------------|-------|
| MTC110 | Mini Toggle Cover Black | £0.15 |
| MTC120 | Mini Toggle Cover White | £0.15 |
| MTC130 | Mini Toggle Cover Red | £0.15 |
| MTC140 | Mini Toggle Cover Blue | £0.15 |
| MTC150 | Mini Toggle Cover Green | £0.15 |
| MTC160 | Mini Toggle Cover Yellow | £0.15 |
| MTC170 | Mini Toggle Cover Grey | £0.15 |

STANDARD TOGGLE SWITCHES

STANDARD TOGGLE SWITCHES standard size toggle switches with solder tag terminals, supplied with On/Off plate. Single pole and double pole options are available.

Rated 1.5A 250V ac. Body dimensions:single pole 25 x 14 x 14mm,



HIGH CURRENT STANDARD TOGGLE SWITCH a high quality standard toggle switch with DPDT centre off action. The switch has screw terminals and a On/Off/On plate. Body dimensions:- 35 x 19 x 19mm.

12mm panel cutout. Rating 6A 250V ac, 10A 125V ac.

| CODE | TYPE | PRICE |
|--------|--------------------------------------|-------|
| STT200 | Standard Toggle DPDT C/Off On-Off-On | £3.99 |

TUMBLER SWITCH

MINIATURE TUMBLER SWITCH a miniature surface mounting SPST (On-Off) toggle switch, that is often referred to as a dolls house switch. Fully chromed actuator

and cover. Connection is made via screw terminals. To be used for low voltages only 12V 3A max.

| CODE | TYPE | PRICE |
|--------|---------------------------------|-------|
| MTS123 | Miniature Tumbler Switch On-Off | £1.65 |

ROCKER SWITCHES

SPST MINIATURE ROCKER SWITCH a miniature single pole rocker switch with black concave rocker which has a red marking which is clearly visible when switch is in the on position. Switch snap fits into a 20mm panel cut-out. 4.8 x 0.8mm fast on connections

6A 250V/ AC

Technical Specification

| Contact rating | 0A 230 V AO |
|----------------------------|---------------------|
| | 10A 125V AC |
| Initial contact resistance | $<$ 50m Ω |
| Insulation resistance | 100M at 500V DC |
| Termination | 4.8 x 0.8mm fast on |
| Operating temperature | -20° to +65°C |
| | |



MINIATURE ROCKER SWITCH DPST a miniature rocker switch with double pole single throw action in a compact package. The on position is clearly marked on the

rocker face. Contacts rated:-4A 250V ac, 8A 125V ac. Panel cut-out 19.2 x 13.2mm.

CODE RS0270

| TYPE | PRICE |
|-------------------------------------|-------|
| Miniature Rocker Switch DPST On-Off | £1.85 |

STANDARD ILLUMINATED ROCKER SWITCH quality rocker switches of modern ergonomic appearance. Matt black bezel with red rocker. Fitted with a neon and resistor giving clear 'on' indica-

tion during 240V ac operation. Panel cut-out

SPST 30 x 10.8mm DPST 30 x 22mm. Contact rating:-10A 250V ac/16A 125V ac.

TYPE CODE

PRICE RSI295 Illuminated STD Rocker Red SPST On-Off......... £1.79 Illuminated STD Rocker Red DPST On-Off......... £2.35 **RSI280**

SLIDE SWITCHES

MINIATURE SLIDE SWITCH a miniature slide switch with solder tag connections with break before make DPDT contacts. Contacts



| CODE | TYPE | PRICE |
|--------|-----------------------------------|--------------|
| SLS400 | Miniature Slide Switch DPDT On-On | £0.30 |

STANDARD SLIDE SWITCHES with solder tag connections, break before make DPDT contacts, and also with centre off. Con-

tacts rating 0.3A 125V ac. Fixinh hole tapped M3 x 3.5mm.

| CODE | TYPE | PRICE |
|--------|--|-------|
| SLS410 | Standard Slide Switch DPDT On-On | £0.30 |
| SLS420 | Standard Slide Switch DPDT C/Off On-Off-On | £0.35 |

MINIATURE PUSH SWITCHES

MINIATURE PUSH TO MAKE SWITCHES miniature low cost push to make switches offered in a variety of colours. Non-locking momentary action - biased to OFF, ideal for operation of solenoids

Rated 250V ac 0.5A Panel cutout 7mm.

| | | V | 1 |
|---------|---------------------|------------------------------|-------|
| CODE | TYPE | | PRICE |
| PTM190 | Push to Make Red | Off-(On) | £0.30 |
| PTM200 | Push to Make Black | k Off-(On) | £0.30 |
| PTM210 | Push to Make Gree | en Off-(On) | £0.30 |
| PTM220 | Push to Make Yello | w Off-(On) | £0.30 |
| PTM230 | Push to Make Blue | Off-(On) | £0.30 |
| PTM240 | Push to Make White | e Off-(On) | £0.30 |
| * PURCH | ASE ANY QUANTITY OF | 10 OR MORE PUSH TO MAKE SWIT | CHES |

IN ANY COMBINATION OF COLOURS FOR £0.25 EACH SWITCH *

MINIATURE PUSH TO BREAK SWITCH a range of miniature low cost switches with opposite action

to push to make action. Dims as above.

| CODE | TYPE | PRICE |
|--------|------------------------------|-------|
| PTB260 | Push to Break Black On-(Off) | £0.45 |

SQUARE PUSH SWITCHES a range of attractive but robust large button push switches with red and black actuator buttons, available in non-locking push to make or SPST latching action. Body dims:-34 x 15 x 15mm. Panel cutout:- 12mm.

Contacts rated 3A 250V ac



| CODE | TYPE | PRICE |
|--------|----------------------------------|-------|
| PTM262 | Square Push to Make Red Off-(On) | £0.90 |
| SLS300 | Latching Switch SP Black On/Off | £1.05 |

TABLE LIGHT SWITCH a single pole push-on push-off switch,

white push button. Panel cutout 10mm, maximum panel thickness 4mm. Body dims:- 24 x 13 x 8.5mm. Rated 2A at 250V ac.



MINIATURE PULL SWITCHES

MINIATURE PULL SWITCH a miniature pull on/pull off switch with

centre pull cord and two fixing holes. Maximum rating 2 amps, 250Vac. Body dimensions:-23 x 13 x 8mm.



| CODE | TYPE | PRICE |
|---------|--|-------|
| 820-242 | Miniature Pull Switch On/Off Centre Cord | £1.69 |

MINIATURE PULL SWITCH a miniature pull on/pull off switch with

side pull cord with one fixing hole. Maximum rating 2 amps 250Vac. Body dimensions 26 x 15 x 11mm.



| CODE | TYPE | PRICE |
|---------|--|-------|
| 820-544 | Miniature Pull Switch On/Off Side Cord | £1.49 |

ROTARY SWITCHES

ROTARY SWITCHES a range of standard pattern skeleton type

rotary switches. Make before break action. Metal shaft, shaft diameter 6mm, length 43mm. Rating 125V ac 250mA.



| TYPE | PRICE |
|-------------------------|--|
| Rotary Switch 1P 12 Way | £1.79 |
| Rotary Switch 2P 6 Way | £1.79 |
| Rotary Switch 3P 4 Way | £1.79 |
| Rotary Switch 4P 3 Way | £1.79 |
| | Rotary Switch 1P 12 Way Rotary Switch 2P 6 Way Rotary Switch 3P 4 Way Rotary Switch 4P 3 Way |

ROTARY SWITCHES a range of standard pattern fully enclosed

rotary switches. Make before break action. Shaft 6.35mm dia x 43mm. Rating 250V ac, 125mA.

| CODE | TYPE | PRICE |
|--------|-------------------------|-------|
| RSW372 | Rotary Switch 1p 12 Way | £1.79 |
| RSW373 | Rotary Switch 2P 6 Way | £1.79 |
| RSW374 | Rotary Switch 3P 4 Way | £1.79 |
| RSW375 | Rotary Switch 4P 3 Way | £1.79 |

BLACK POINTER KNOB black pointer knob with a white indicator

line, for use with 6mm and 6.35mm (0.25") shafts. Grub screw fixing.

| CODE | TYPE | PRICE |
|--------|--------------|-------|
| RSK390 | Pointer Knob | £0.50 |

MATT BLACK CONTROL KNOBS a range of matt black control

knobs with use with 6mm shafts. Grub screw fixing, available in a range of sizes.

| | | | • | | | |
|---------|-----------------|---------|----------|--------|---|-------|
| CODE | TYPE S | Spindle | Dia | Height | t | PRICE |
| 600-700 | Matt Black Knob | 6mm | - 15.0 x | 14mm. | | £0.39 |
| 600-705 | Matt Black Knob | 6mm | - 19.5 x | 15mm. | | £0.55 |
| 600-710 | Matt Black Knob | 6mm | - 24.0 x | 20mm. | | £0.65 |
| 600-715 | Matt Black Knob | 6mm | - 35.0 x | 17mm. | | £0.75 |


MICRO SWITCHES

SUB-MINIATURE MICRO SWITCHES a range of new generation sub-miniature micro switches which offer a 1A 250V ac switching ability in a miniature package. 2 types available, single pole changeover contacts. Miniature solder terminals.

| Contact material | Silver alloy | | 4.4 |
|--------------------|---------------------|------------|---------------|
| Contact rating | 2A 30V dc, | 1A 250V ac | 11.2 |
| Mechanical life | >30x10 ⁴ | | 1.5 OP |
| Electrical life | >30x10 ⁴ | | ÷ L |
| | | | 3.5 |
| | Button | Lever | 5.08 5.08 1.0 |
| Operating force | 150g | 80g | 12.8-4 |
| Release force min. | 20g | 5g | 1=0.3 |
| Pretravel max. | 0.5mm | - | FF ATT |
| Overtravel min. | 0.25mm | 0.55mm | OP OP |
| Movement diff. max | 0.12mm | 0.5mm | |
| Actuator length | - | 13mm | Ψ и и и |

| CODE | TYPE | PRICE |
|--------|----------------------------------|--------------|
| MMS450 | Sub-Miniature Microswitch Button | £0.99 |
| MMS460 | Sub-Miniature Microswitch Lever | £0.99 |


MINIATURE MICRO SWITCHES a range of V4 miniature single pole changeover micro switches, incorporating a long life stainless steel spring system and precious metal contacts. Rated 5A 250V



| | Operating | Pre-travel | Overtravel | Movement | Actuator |
|---------|-----------|------------|------------|--------------|----------|
| | force | (max) | (min) | differential | length |
| Button | 90g | 0.6mm | 0.5mm | 0.1mm | - |
| Lever | 42g | 0.6mm | 1.0mm | 0.6mm | 14.5mm |
| L/Lever | · 25g | 4.7mm | 1.0mm | 1.8mm | 43.0mm |
| Roller | 42g | 2.6mm | 1.0mm | 0.6mm | 14.5mm |

| CODE | TYPE | PRICE |
|--------|-------------------------------|-------|
| MSB470 | Mini Microswitch Button | £0.90 |
| MSL480 | Mini Microswitch Lever | £0.95 |
| MSL490 | Mini Microswitch Long Lever | £1.10 |
| MSR500 | Mini Microswitch Roller Lever | £1.10 |

STANDARD MICRO SWITCHES high quality V3 standard size SPDT micro switches, offering a switching capacity of 10A 250V ac. Connections may be made by either a 1/4" connector or soldering.



| CODE | TYPE | Operating Force | PRICE |
|--------|------------------------------|-----------------|-------|
| SMSB06 | Standard Microswitch Button | 285g | £0.99 |
| SMSL15 | Standard Microswitch Lever. | 130g | £0.99 |
| SMSR45 | Standard Microswitch Roller. | 140g | £1.25 |

REED SWITCHES

REED SWITCH a range of dry reed switches with rhodium plated contacts for long life. When a magnet or electromagnet is brought near the reed, magnetism is induced which causes the switch to close. When the operating magnet is removed, the springiness of the reed reverses the action. 8 types are available for a wide range of applications. Sold individually.

| Case | | | | |
|------|----|------|------|------|
| code | Α | В | С | D |
| 1 | 36 | 10 | 2.0 | 0.4 |
| 1A | 46 | 15 | 2.54 | 0.6 |
| 2 | 55 | 14 | 2.3 | 0.5 |
| 3 | 52 | 14 | 2.6 | 0.5 |
| 4 | 55 | 14 | 2.2 | 0.35 |
| 6 | 55 | 18.5 | 2.6 | 0.7 |
| 8 | 79 | 52 | 5.4 | 2.5 |
| | | | | |



Switching Switching Pull in

A = Overall length,B = Glass lengthC = Diameter,D = Lead diameter

Contact

| | | | - Ciliaci | •g | • | 9 · u | |
|-------|-------------|------|-----------|---------|---------|-------|---------|
| | | | Rating | Current | Voltage | range | |
| Type | | Case | VA Max | A Max | AC max | (AT) | Code |
| Micro | SPST | 1 | 1.0 | 0.1 | 24 | 10-30 | 820-800 |
| Sub | SPST | 2 | 10.0 | 0.5 | 100 | 15-35 | 820-805 |
| Sub | SPDT | 3 | 3.0 | 0.2 | 30 | 15-30 | 820-810 |
| Sub | SPST | 4 | 10.0 | 1.0 | 250 | 10-30 | 820-815 |
| Mini | SPST | 1A | 10.0 | 0.5 | 140 | 14-23 | 820-820 |
| Mini | SPST | 6 | 40.0 | 2.0 | 440 | 14-23 | 820-825 |
| Comp | SPST | 8 | 120.0 | 3.0 | 1500 | 75-95 | 820-835 |
| | | | | | | | |

| CODE | TYPE | PRICE |
|---------|--------------------------------|--------------|
| 820-800 | Micro Reed Switch SPST | £1.55 |
| 820-805 | Sub-miniature Reed Switch SPST | £1.05 |
| 820-810 | Sub-miniature Reed Switch SPDT | £4.79 |
| 820-815 | Sub-miniature Reed Switch SPST | £1.99 |
| 820-820 | Miniature Reed Switch SPST | £1.35 |
| 820-825 | Miniature Reed Switch SPST | £2.35 |
| 820-835 | Compact Reed Switch SPST | £5.25 |

REED SWITCH a low cost dry reed switch with rhodium plated contacts for long life. When a magnet or electromagnet is brought near the reed, magnetism is induced which causes the switch to close. When the operating magnet is removed, the springiness of the reed breaks the contact. Contact rating 0.5A ac or dc, switching voltage 200V dc or 125V c max. Glass length 27mm x 3.5mm.

| CODE | TYPE | PRICE |
|--------|---------------------------------------|-------|
| RES430 | Reed Switch 10 Pack | £1.50 |
| MPM120 | Reed Switch Operating Magnets 10 Pack | £1.50 |

MAGNETS

MINIATURE MAGNETS a range of select miniature magnets suitable for use with above reed switches. Supplied individually.

| Code | Length Width Depth | |
|---------|--|----------------|
| 820-850 | 12.7 x 3.2 x 1.6mm | |
| 820-855 | 19.0 x 3.2 x 3.2mm | |
| 820-860 | 28.0 x 4.8 x 4.8mm | |
| 820-865 | 25.4 x 6.4 x 6.4mm | |
| CODE | TYPE | PRICE |
| 000 050 | | |
| 820-850 | Miniature Magnet 12.7 x 3.2 x 1.6mm | £0.45 |
| 820-850 | • | |
| | Miniature Magnet 19.0 x 3.2 x 3.2mm | £0.99 |
| 820-855 | Miniature Magnet 19.0 x 3.2 x 3.2mm Miniature Magnet 28.0 x 4.8 x 4.8mm | £0.99 £1.80 |

MAGNETS a range of disc magnets manufactured from Neodymium iron Boron which is up to 5 times more powerful than Alnico. Magnets are nickel plated to reduce the onset of corrosion when used under normal circumstances. Ideally suited to proximity

switchtriggering or biasing where space is at a premium.

M1219-1

Technical Specification

| Distance at which | | | | | |
|-------------------|---------|--------------|--|--|--|
| magnets mea | sure | | | | |
| 1000 gauss | Dims | Surface flux | | | |
| 4.1mm | 3 x 1mm | 1500 | | | |
| 2.2mm | 3 x 2mm | 2500 | | | |
| 1.8mm | 4 x 3mm | 3200 | | | |

(gauss)

 M1219-2
 2.2mm
 3 x 2mm
 2500

 M1219-3
 1.8mm
 4 x 3mm
 3200

 M1219-4
 1.2mm
 6 x 2mm
 2500

 M1219-5
 0.6mm
 10 x 5mm
 3500

 Operating temperature
 120°C max.


NB M1219-4 has north seeking identified with a dimple.

| CODE | TYPE | PRICE |
|---------|-------------------------|--------------|
| 820-507 | Magnet 3 x 1mm M1219-1 | £0.79 |
| 820-509 | Magnet 3 x 2mm M1219-2 | £0.80 |
| 820-510 | Magnet 4 x 3mm M1219-3 | £0.89 |
| 820-512 | Magnet 6 x 2mm M1219-4 | £0.99 |
| 820-514 | Magnet 10 x 5mm M1219-5 | £1.39 |

MODEL RAILWAY ELECTRIC'S

MODEL RAILWAY ELECTRIC'S BOOK by Fred Martin, a guide

to wiring a model railway for the novice and experienced modeller alike. The book covers wiring for cab control, points, point motors, layout planning, wiring multiple baseboards, passive sections, fiddle yards and reversing.



| CODE | TYPE | PRICE |
|---------|-------------------------|-----------|
| 500-999 | Model Railway Electrics | £5.00 |

STRIP BOARD & MATRIX BOARD

MATRIX BOARD matrix board, similar to strip board, with holes


punched on a 0.1" matrix but without the copper strips on the underside. Manufactured in SRBP and therefore may be easily cut to down to any size that is required.



| CODE | TYPE | PRICE |
|---------|--|-------|
| 601-530 | Matrix Board 95 x 127mm. 36 x 50 Holes | £2.35 |

STRIP BOARD a range of sizes of fully pierced stripboard used for prototype, development work and hobby work etc. it can be readily cut down to any size. Provides a simple base on which to build cir-

cuits with interconnections formed by copper strips which may be cut as desired, manufactured from copper clad laminated board and the holes are pierced on a 0.1" pitch.



| CODE | TYPE | | PRICE |
|---------|-----------------|---------------------|--------|
| 601-500 | Stripboard 0.1" | 25 x 64mm | £0.39 |
| 601-505 | Stripboard 0.1" | 64 x 95mm | £1.29 |
| 601-510 | Stripboard 0.1" | 95 x 127mm | £2.49 |
| 601-515 | Stripboard 0.1" | 95 x 432mm | £8.50 |
| 601-520 | Stripboard 0.1" | 119 x 455mm | £10.99 |
| 601-560 | Terminal Pins S | Single Ended 100 Pk | £1.45 |

STRIP BOARD TRACK CUTTER used for track cutting of strip board tracks. Insert the tool at the point where a break is required and twist clockwise.

| CODE | TYPE | PRICE |
|---------|-------------------------|-------|
| 601-550 | Stripboard Track Cutter | £4.75 |

CLOCK MOVEMENTS

QUARTZ CLOCK MOVEMENTS a range of high quality quartz clock movements with dust proof and moisture resistant case. The case has an integral hanger, the hands can be adjusted from the side or rear of the movement. 3 types are available for use with clock casing of up to 5mm, 12.5mm and

17mm. Case size:- 55 x 55 x 15mm.



PENDULUM CLOCK MOVEMENTS

QUARTZ PENDULUM CLOCK MOVEMENT a high quality pendu-

lum quartz clock movement with dust proof and moisture resistant case. The case has an integral hanger, the hands can be adjusted from the side or rear of the movement. Supplied without pendulum.



| CODE | TYPE | PRICE |
|---------|--------------------------------|-------|
| 860-117 | Quartz Pendulum Clock Movement | £8.99 |

BRASS PENDULUM an adjustable brass pendulum for use with the above clock movement. Length 300mm.



ALARM CLOCK MOVEMENT

QUARTZ ALARM CLOCK MOVEMENT WITH HANDS a high quality quartz clock movement with alarm function. The case is

dust proof and moisture resistant. The case requires to be glued to the face. Supplied with 4 hands:- hour 38mm, minute 48mm, second 42mm and alarm pointer 23mm.



| CODE | TYPE | PRICE | |
|---------|--|-------|--|
| 860-726 | Quartz Alarm Clock Movement With Hands | £8.45 | |

CENTRE NUT SPANNER

CENTER NUT SPANNER a special tool for tightening and releasing the central screw of clock movements.



| CODE | TYPE | PRICE |
|---------|--------------------|-------|
| 860-128 | Center Nut Spanner | £6.99 |

CLOCK HANDS

CLOCK HANDS STRAIGHT BLACK a pair metal clock hands for use with above clock movements (not alarm movement). Length hour/minute:- 35/25mm.

CODE TYPE PRICE
860-050 Clock Hands Straight Black H/M 35/25mm............ £2.15

CLOCK HANDS POINTED a pair metal clock hands for use with above clock movements (not alarm movement). Length hour/minute:- 65/45mm. Available in Black.



| CODE | TYPE | PRICE |
|---------|---------------------------------------|-------|
| 860-139 | Clock Hands Pointed H/M 65/45mm Black | £2.85 |

CLOCK HANDS PARALLEL POINTED a pair metal clock hands for use with above clock movements (not alarm movement). Length hour/minute:- 60/46mm.

TYPE PRICE
Clock Hands Parallel Pointed H/M 60/46mm..... £3.20

CLOCK HANDS STRAIGHT a pair metal clock hands for use with above clock movements (not alarm movement). Length hour/minute:- 80/60mm. Available in Black.



CODE TYPE PRICE 860-151 Clock Hands Straight H/M 80/60mm Black.............. £3.65

CODE

860-140

PRICE

£3.65

CLOCK HANDS ANTIQUE SMALL a pair metal clock hands for use with above clock movements (not alarm movement). Length hour/minute:- 60/42mm. Available in Black.



CODE TYPE PRICE 860-162 Clock Hands Antique Small H/M 60/42mm Black. £3.75

CLOCK HANDS a pair metal clock hands for use with above clock movements (not alarm movement). Length hour/minute:-85/65mm.



CLOCK HANDS CURVED a pair metal clock hands for use with above clock movements (not alarm movement). Length hour/minute:- 80/63mm.



SECOND HANDS "WIGGLEY" a metal second hand for use with above clock movements (not alarm movement). Radius 60mm and 90mm.



SECOND HAND CURVED a metal second hand for use with above clock movements (not alarm movement). Radius 80mm.



QUARTZ CLOCK MOVEMENT CAP for use with above clock movement when second hand is not used.

Not required for alarm movement.

CODETYPEPRICE860-195Quartz Clock Movement Cap......£0.99

WHEN PLACING AN ORDER PLEASE USE THE FULL ORDER CODE INCLUDING ANY PUNCTUATION

MINIMUM ORDER VALUE £15.00

CLOCK FACES AND NUMERALS

CLOCK FACE CARD a card face for use with above clock move-

ments. Black figures on white card. Diameter 120mm.



| CODE | TYPE | PRICE |
|---------|---------------------------|--------------|
| 860-210 | Clock Face Card 120mm Dia | £0.99 |

CLOCK FACE BRASS ANODISED a brass anodised face for use

with above clock movements. Black figures on brass face. Diameter 120mm.




| CODE | TYPE | PRICE |
|---------|-------------------------------------|-------|
| 860-209 | Clock Face Brass Anodised 120mm Dia | £5.85 |

CLOCK NUMERAL SET self-adhesive backed numerals in black.

Figure height 16mm

CLOCK NUMERAL SET self-adhesive backed clock numerals in Gold.

MDF CLOCK BLANKS handy wooden clock face blanks, great for painting and decorating with your own design. Suitable for use with most clock mechanisms. Circle diameter: 170mm, Square size: 170 x 170mm. Sold individually.



| CODE | TYPE | | PRICE |
|---------|----------------------|---------------|-------|
| 860-782 | MDF Clock Face Blank | Square Single | £1.50 |
| 860-780 | MDF Clock Face Blank | Round Single | £1.90 |

FREE PARKING FOR 2 HOURS
OUTSIDE OF OUR SHOP